


ALLEGRO™ DOOR PULLS

PRODUCT DATA








PRODUCT DATA

Allegro Door Pulls create an elegant opening statement. Available in a variety of shapes and sizes, pulls are cast of solid Stainless Steel or Bronze. Robust finishes enhance each form and add to the visual richness of the collection.


MATERIALS & FINISHES

INSTALLATION & MAINTENANCE

STAINLESS STEEL		BRONZE		INSTALLATION	MAINTENANCE	
US32	Polished Stainless Steel	US9	Polished Bronze	Allegro Door Pulls may be single mounted or mounted back-to-back on wood, metal or glass doors.	Allegro Door Pulls are well-suited for interior or exterior use. Regular maintenance will help ensure the lasting beauty of each pull.	
US32D	Satin Stainless Steel	US10	Satin Bronze			
SSS	Stippled Stainless Steel	SBR	Stippled Bronze	Allegro Door Pulls are installed using Mounting System "B". A thread-locking adhesive such as Loctite® is		
US		US10B	Oil-Rubbed Bronze	recommended for secure installation. Refer to Mounting	For more information, please refer to <i>Door Hardware Care &</i>	
		S10	Stippled Oil-Rubbed Bronze	Options B1, B2, B3, B4, B5, B6 and B7 shown below for additional information.	Maintenance found on our website.	



MOUNTING OPTIONS



For more information on mounting Allegro Door Pulls, please refer to the Hardware Installation Instruction Manual found on our website.









T 1.800.451.0410 | F 412.781.7840 | www.forms-surfaces.com





PRODUCT DATA

LIST PRICING AND ORDERING INFORMATION

Pricing does not include freight. No additional charge for mounting hardware. All pricing is for single units, not pairs.

MODEL	STAINLESS STEEL		BRONZE	
DP7701 End Cap; 2" (51mm) dia.	US32, US32D, SSS	\$74	US9, US10, SBR, US10B, S10	\$100
DP7751 Straight; 12" (305mm) c.c.	US32, US32D, SSS	\$463	US9, US10, SBR, US10B, S10	\$695
DP7751 Straight; 20" (508mm) c.c.	US32, US32D, SSS	\$613	US9, US10, SBR, US10B, S10	\$919
DP7753 Offset; 12" (305mm) c.c.	US32, US32D, SSS	\$463	US9, US10, SBR, US10B, S10	\$695
DP7753 Offset; 20" (508mm) c.c.	US32, US32D, SSS	\$613	US9, US10, SBR, US10B, S10	\$919
DP7758 S-Shape-Left; 20" (508mm) c.c.	US32, US32D, SSS	\$613	US9, US10, SBR, US10B, S10	\$919
DP7759 S-Shape-Right; 20" (508mm) c.c.	US32, US32D, SSS	\$613	US9, US10, SBR, US10B, S10	\$919

HOW TO SPECIFY:

Provide model number, center-to-center (c.c.) dimension, quantity, metal and finish, mounting option, door material and thickness.







T 1.800.451.0410 | F 412.781.7840 | www.forms-surfaces.com