



4500

Series electric strike



shown with mortise tab option



fire rated



field selectable
(12 or 24VDC)



grade 1



Specially designed to accommodate 2" fire-rated frames

The versatile, low profile, heavy duty, fire-rated solution

The 4500 series is the first electric strike designed for installation in 2" UL 10C fire-rated frames with 1/2" drywall penetration. Based on the design of the popular 5000 series, the 4500 electric strike features a low profile 1-3/8" depth, heavy-duty cast stainless steel construction and horizontal adjustment for simple installation. Its strength is derived from a unique keeper pin locking design, enabling the 4500 to exceed the ratings of the frame, door and locking hardware. Designed for use with cylindrical and mortise locksets up to a 3/4" throw.

Specifications

- UL 10C fire rated, 3 hour (fail secure only)
- CAN4-S104 (ULC-S104) fire door conformant
- WHI fire door listed
- ANSI/BHMA A156.31, Grade 1 (#E09321, #E09322, #E09323)
- NFPA-252 fire door conformant
- ASTM-E152 fire door conformant
- California Fire Marshall Listed
- UBC-7-2-94, Uniform Building Code
- Patented design

Frame application

- Steel
- Aluminum
- Wood

Electrical

- .24 Amps @ 12VDC/VAC
- .12 Amps @ 24VDC/VAC
- DC continuous duty/AC intermittent duty only

NOTE: Relocation of the strike prep may be required for Schlage L Series and Yale 8700 mortise locks. Consult HES customer support regarding use with Best 40 Series.

cylindrical locksets



mortise locks without deadbolts





4500

Series electric strike




diagram shown with cylindrical tab option

Standard Features

- Stainless steel construction
- Tamper resistant
- Static strength 3,000 lbs.
- Dynamic strength 70 ft-lbs.
- Endurance 500,000 cycles
- Fail secure (standard)
- Dual voltage 12 or 24 VAC/VDC
- Horizontal adjustment
- Multiple tabs included to accommodate a variety of locksets
- Non-handed
- Internally mounted solenoid
- Accommodates up to a 3/4" latchbolt
- Strike body depth 1-3/8"
- Plug-in connector
- Trim enhancer
- Five year limited warranty

Optional Features

- Fail safe
- LBM - Latchbolt monitor
- LBSM - Latchbolt strike monitor
- Extended lip models available (1/2", 1" and 2")

Accessories

- 4500 - 105 Trim Enhancer Blk
- 4500 - 131 - Filler block - 7/16"
- 154 - MTK Metal template kit
- 2001 - Plug-in bridge rectifier
- 2004 - ElectroLynx® adapter
- 2005 - SMART Pac II™
- 2006P - Plug-in buzzer
- 2009P - Plug-in LED

Finishes

- 630 - Satin stainless steel finish
- 605 - Bright brass finish
- 606 - Satin brass finish
- 612 - Satin bronze finish
- 613 - Bronze toned finish
- 629 - Bright stainless steel finish