




A heavy-duty version of the 7000 series, the 7400 is constructed from all stainless steel components and hardened stainless steel locking cams. The model 7400 can accommodate a variety of rim exit devices up to 3/4" pullman latch. The 7400 is field selectable from fail secure to fail safe and can operate up to 30 lbs. of door loading (fail secure operation).



Specifications:

- UL 1034, burglary resistance
- ANSI/BHMA 156.31, Grade 2
- ASTM specification E152
- NFPA specification 252
- Patent #5,484,180

Electrical:

- .45 Amps @ 12VDC
- .25 Amps @ 24VDC

Standard Features:

- High durability
- Tamper resistant - heavy duty construction
- Fail secure standard
- Field selectable fail secure / fail safe
- 30lbs. of door resistance (fail secure)
- Non-handed

- Internally mounted solenoid
- Patented design
- 3 year limited warranty

Optional Features:

- 7000-106 - keeper pocket adapter
- 7000-108 - spacer plate
- 7000-783SMB - surface mounting box
- LBM - Latchbolt monitor
- 2001 - Plug-in bridge rectifier
- 2005 - SMART Pac II™ power controller
- 2505 - Power Punch™ power supply
- 2006P - Plug-in buzzer
- 2009P - Plug-in L.E.D.


Finishes

- 605 Bright brass
- 606 Satin brass
- 612 Satin bronze
- 613 Bronze toned
- 630 Satin stainless steel (standard)
- 651 Polished chrome

7483 Model

Operation: After releasing pullman latch, the keeper returns to the locked position.

type of lock released



9" x 1-3/4" x 11/16"

7483

For use with

rim panic exit devices in metal jambs with up to a 3/4" pullman latch. Metal or wood frames.

Compatible Locksets:

American Device, Arrow, Doramatic, Monarch, Precision, Sargent, Von Duprin, Yale


ANSI/BHMA #EO9312



7486 Model

Operation: After releasing pullman latch, the keeper returns to the locked position.

type of lock released



6-1/2" x 1-3/4" x 1/2"

7486

For use with

rim panic exit devices in aluminum jambs and surface mounted vertical rod exit devices with up to a 3/4" pullman latch. Aluminum frames.

Compatible Locksets:

Adams Rite, American Device, Arrow, Doramatic, Jackson, Monarch, Precision, Sargent, Von Duprin, Yale


ANSI/BHMA #EO9312



7489 Model

Operation: After releasing pullman latch, the keeper returns to the locked position.

type of lock released



9" x 1-3/4" x 1/2"

7489

For use with

rim panic exit devices in aluminum jambs with up to a 3/4" pullman latch. Aluminum frames.

Compatible Locksets:

Adams Rite, American Device, Arrow, Doramatic, Jackson, Monarch, Precision, Sargent, Von Duprin, Yale

ANSI/BHMA #EO9312

