

SE SERIES 212se, 232se, SS-KP500wp, 272wp

SEALED ENVIRONMENTAL KEYPAD

- □ Surface mount single gang
- □ 212 style 4 SPDT relays
- Vandal resistant
- Metal Braille Keys
- Weatherproof, self-conitained metal housing
- □ 4.5" x 3.0" x 1.55"
- □ 10-30 VDC; 12-24 VAC auto adjusting
- Optional printer interface

The 212 Series keypads are designed for basic access control or code control for up to four individual devices (model dependent). These keypads are the perfect choice for controlling electric or magnetic locks, security systems, elevator control, gate controls, or other types of equipment requiring on/off or momentary control inputs.

FEATURES

- □ 120 users
- Input trigger for Request to Exit or other open circuit contact
- Up to 4 independent outputs (model dependent)
- All outputs programmable for latched or timed operation.
- Keypad programmable

The 232 Series keypads are designed to meet most residential, commercial, and industrial single door access control requirements. Each 232 Keypad provides two inputs and four outputs, factory set access control.

FEATURES

- 120 users
- Request to Exit input
- □ Door Monitoring input
- Relay outputs
 - Lock release
 - o Door forced
 - Door propped
 - Alarm shunt
- □ Keypad programmable

SECURED SERIES

A Secured SeriesTM Access Control Systems with Hub ManagerTM Professional Access Control Software is a smart and easy to use solution for small to midsize applications.

Fast and powerful management reports meet the requirements of the mainstream commercial access control market and Hub Manager Professional Software uses access levels for construction of logical groupings of doors, sites, and time zones.

Hub Manager Professional features a set of programming wizards that make system set up and system modifications easy for the end-user. Build new access levels, construct remote sites, add door after door, add operators and set privileges – the most complex operations for other access control systems – are made easy with Hub Manager Professional's programming wizards.

FEATURES:

- □ 10,000 users system-wide
- Unlimited access levels
- Easily produce management reports
- □ 1,000 users per door
- □ Microsoft Windows 98/2000/XP
- 2,000 users with prox.pad plus and LS2/2P access control locksets
- Remote management via modem or LAN/WAN
- □ Easy to use set up wizards
- User list import wizard
- Password base software access
- Time and attendance feature
- □ 32 Doors per site
- □ 1,000 sites

SE SERIES - Continued 272wp



WIEGAND SERIES

IEI Wiegand Series Keypad offers multiple keypad styles in both IEI IM proprietary reader communication protocol and standard Wiegand communication protocol.

FEATURES

- □ Works with most manufacturers systems
- □ 4 wire connection for IEI IM protocol
- □ 5 wire connection for standard Wiegand protocol
- ☐ User configurable to conform to multiple Wiegand formats with even parity
 - o KP Series IEI Proprietary Protocol
 - o 272 Series Wiegand Protocol
 - SSW Series User Selectable IEI or Wiegand Protocol