



# ROFU® ELECTRIC STRIKE MODEL 1960/3960

1960 AND 3960 - SERIES, WITH FACEPLATE 1 3/4" x 9 1/2"

**Model 1960** — Fail - Secure. (Non Fail - Safe)

**Model 3960** — Fail - Safe

Electric Strike for Rim Exit Devices  
For Commercial, New or Retrofit Uses.



**1960/3960  
Non-Handed**

## Standard Features

- 9 1/2" x 1 3/4 " Stainless Steel Faceplate
- Heavy Duty & Tamper Resistant Design
- Stainless Steel Keeper
- "PK" Keeper Design
- Tamper Strength 1500 lbs
- Cycle Test 500,000
- Reversible – Non-Handed
- Horizontal Adjustment
- Built in MOV for Spike Suppression
- 5/8" Thick Faceplate
- 1/8" Faceplate Spacers (*2 Supplied*) to Allow Full Engagement of Locking Latch
- Mounting Hole Locations Positioned for Durable Installations
- Integrated Non-Handed Ramps for Dead Locking Latch Bolt Function
- Limited Warranty - **36 Months**

## Available in the following Voltages and Finishes:

Finish	xUS32D
Voltage, Fail Secure	x05=12VAC/12VDC x08=24VAC/24VDC
Voltage, Fail Safe	x06=12VDC x09=24VDC





**Line Art for 1960**

**HOLLOW METAL JAMB PREPARATION**

