



692 Series

SmartBar™



Overview

The 692 SmartBar is an electronic switching device with no moving parts, which serves as a non-latching request-to-exit bar at an egress door. It allows one motion egress at doors equipped with electromagnetic or electronic locks, with “no prior knowledge” required by the user. Touching the SmartBar at any point on the bar activates internal circuitry which controls power to the locking device. No moving parts results in low maintenance and long life.

The 692 SmartBar provides two directionally opposed infrared detection circuits to sense an exit request. As a person touches the bar, the light beam is broken. The patent-pending redundant system provides a high level of life safety and peace of mind to the end user.

An audible alarm is standard. This feature provides a security alarm to alert when there is a prolonged unlocked condition caused by a continued break in the light beam. This feature is desirable in applications requiring monitoring of security conditions or delayed egress.

- Dual Infrared detection circuits, patent-pending
- No moving parts – one motion egress
- Audible alarm standard, alerts prolonged unlock condition
- DPDT relay standard – single access control panel or auxiliary device

Features and benefits

- Heavy-duty aluminum extrusion with cast metal end caps - maximum durability
- Field reversible, field sized
- Quick install brackets / universal mounting system for aluminum, hollow metal and wood doors
- Low profile for greater clearance through door
- “PUSH TO EXIT” signage designates opening
- Glow in the dark “PUSH TO EXIT” option

692 SmartBar electrical specifications

Input voltage	12 or 24 VDC maximum current draw .5 amps
Switch	DPDT contacts rated 4 amps @ 30 VDC
Wiring	8 conductor cable - 20 AWG (standard)

Ordering information

Door size

- 36", 42" or 48"

Finishes

- **628** - Satin anodized aluminum (standard)
- **313** - Dark satin bronze anodized aluminum

TouchPads

- **RD** - Black with red "PUSH TO EXIT"
- **GID** - Black with glow in the dark "PUSH TO EXIT"

Handing

- **RHR** - Right hand reverse
- **LHR** - Left hand reverse - field reversible

Options

- **WD** - Sexnut door kit for heavy-duty wood door and hollow metal door applications
- **SHK** - Aluminum door mounting shim kit includes brackets, shims and screws for narrow stile aluminum doors.*

* Screw pack has self-drilling and self-tapping screws for aluminum and wood door applications and rivnuts for hollow metal door applications.

Note: 18" x 1/2" armored door cord shipped standard.

Allegion, the Allegion logo, Schlage, and the Schlage logo are trademarks of Allegion plc, its subsidiaries and/or affiliates in the United States and other countries. All other trademarks are the property of their respective owners.

About Allegion

Allegion (NYSE: ALLE) creates peace of mind by pioneering safety and security. As a \$2 billion provider of security solutions for homes and businesses, Allegion employs more than 7,800 people and sells products in more than 120 countries across the world. Allegion comprises 23 global brands, including strategic brands CISA®, Interflex®, LCN®, Schlage® and Von Duprin®. For more, visit www.allegion.com.

aptiQ ■ LCN ■  ■ STEELCRAFT ■ VON DUPRIN



© 2014 Allegion
003904, Rev. 02/14
www.allegion.com/us