



800 Series

Remote and local monitoring stations



800 Series

Local and remote monitoring station

The 800 Series monitoring stations can provide monitoring for a single zone with up to 2 LED indicators.

801 Series

Local and remote monitoring station

The 801 unit includes an audible and visual indication of lock status and delay activation. Interfaces with electromagnetic locks with magnetic bond sensor (MBS) option. Unit mounts in a standard single gang electrical box.

The 801-KS fulfills a code requirement stating that a local signal assures users that a delayed egress system is functional. The unit includes an audible and visual indication of lock status and delay activation. Provides a Single Pole, Double Throw (SPDT) momentary x SPDT maintained contact arrangement keyswitch for legal release and reset of the system, which interfaces with a standard 1 1/4" mortise cylinder with standard straight cam. Interfaces with electromagnetic locks with Magnetic Bond Sensor (MBS) option. Unit mounts in a standard double gang electrical box.

Features and benefits

- 800 Series local and remote monitoring station
 - Up to 2 LED indicators
- 801 Series local and remote monitoring stations
 - 801-KS option

800 specifications

Operating power	12/24 VDC
LED Operating power	6-28 VDC
LED current draw	30 mA ea.
Audible input	10-28 VDC
Audible current draw	3-14 mA
Decibel rating	80 dB @ 2 ft
Single gang unit	
Length	2 3/4"
Width	1 1/2"
Height	4 1/2"
Finish	Stainless steel
800L1	One (1) LED Indicator - red, green, and amber
800L2	Two (2) LED Indicators - red, green, and amber
800A	Audible sounder

801 specifications

Operating power	12/24 VDC
LED operating power	6-28 VDC
LED current draw	30 mA ea.
Audible input	10-28 VDC
Audible current draw	3-14 mA
Decibel rating:	80 dB @ 2 ft
Single gang unit	
801* Local or remote monitoring system	
Length	2 3/4"
Width	1 1/2"
Height	4 1/2"
Finish	Stainless steel
Double gang unit	
801-KS* local or remote monitoring system with keyswitch (less cylinder)	
Length	4 9/16"
Width	1 15/16"
Height	4 1/2"
Finish	Stainless steel
Keyswitch contacts	5A/250 VAC

*Note: 801/801-KS requires MBS on locking device.

Allegion, the Allegion logo, Schlage, and the Schlage logo are trademarks of Allegion plc, its subsidiaries and/or affiliates in the United States and other countries. All other trademarks are the property of their respective owners.

About Allegion

Allegion (NYSE: ALLE) creates peace of mind by pioneering safety and security. As a \$2 billion provider of security solutions for homes and businesses, Allegion employs more than 7,800 people and sells products in more than 120 countries across the world. Allegion comprises 23 global brands, including strategic brands CISA®, Interflex®, LCN®, Schlage® and Von Duprin®. For more, visit www.allegion.com.

aptiQ ■ LCN ■ **SCHLAGE** ■ STEELCRAFT ■ VON DUPRIN



© 2014 Allegion
005007, Rev. 02/14
www.allegion.com/us