

SCHLAGE

Integrated security solution

bright blue[®] and AD Series electronic locks

Overview

Looking for a security solution that is affordable, flexible and easy to install and manage? Vanderbilt Industries **bright blue**[®] and Schlage have teamed up to provide web-based access management with integrated electronic locks to deliver a cost effective solution ideal for small to medium sized facilities.

With the **bright blue**[®] access control system from Vanderbilt Industries, changes such as adding or deleting users can be made from virtually any laptop or desktop computer. The **bright blue**[®] system features a user friendly interface, standardized reports and video integration; your system can be up and running in no time at all.

Installation of the hardware is simplified since Schlage AD Series integrated locks combine all of the components typically found around the door, such as the credential reader door position switch and the request-to-exit switch. Designed to be modular, Schlage AD Series locks can easily be upgraded in the future to meet your changing security and technology requirements.

By electronically scheduling lock and unlock times you will improve security and productivity. By issuing electronic credentials, like aptiQ[™] smart cards, you not only know who gained access where and when but you reduce the costs associated with re-keying. When you invest in electronic access control within your facility you increase security, add convenience and save money over time.

AD-301 and AD-401 FIPS 201-1 compliant solutions available using FMK readers. Existing AD-300 and AD-400 locks can be upgraded to FIPS compliant solutions by replacing existing reader with new FMK reader. Please contact Vanderbilt to confirm they will be able to support your FIPS 201 credential format.



System Capabilities

- bright blue[®] supports up to 32 doors and up to 5,000 users
 - Convenient web-based application
 - Remote access and administration
 - No software to install and no dedicated PC required
 - Holiday and event scheduling
 - Facility lockdown via credential or external push-button
 - Event notification via email and text
 - Degraded mode
 - Video management options
- For AD-400 wireless applications:
 - Communicates to the bright blue[®] controller via PIM400-485-VBB (RS-485); each supports up to 16 devices
 - 900 MHz communication between AD-400 and PIM400 for secure, encrypted transmission
- Patent-Pending Wireless Lockdown feature (10 seconds or less) preserves 2 year battery life
- For AD-300 hardwired applications:
 - Directly communicates via RS-485 connection to the **bright blue**[®] panel
- Additional details on readers supported and chassis types available on page 3 and 4
- Supports classroom/storeroom function
 - Office function supported with RS-485 connection only
- AD Series: ANSI/BHMA A156.25, ANSI/BHMA Grade 1, UL 294, UL 10C

AD-400/401 via RS-485 with bright blue®

- bright blue[®] controller supports up to 32 RS-485 devices (AD-300/301 and AD-400/401 combined)
- bright blue[®] controller supports a maximum of 16 PIM400-485-VBB per RS-485 port
- There are 32 RS-485 ports on each bright blue[®] controller
- Wireless range up to 200' in typical building construction, up to 1000' line of sight

Note: Although not specifically shown, both AD-300/301s and AD-400/401s can be managed on a common RS-485 port.









Software rev 2.1.1 or higher for WRI-400 rev 3.1.X or higher

bright blue® panel

PIM400-485-VBB Panel interface model AD-400/401 Wireless devices

Wireless devices

AD-300/301 via RS-485 with bright blue®

- bright blue[®] controller supports up to 32 RS-485 devices (AD-300/301 and AD-400/401 combined)
- bright blue[®] controller supports a maximum of 16 PIM400-485-VBB per RS-485 port
- There are 32 RS-485 ports on each bright blue[®] controller



Note:

Please refer to AD-300, AD-301, AD-400, AD-401, PIM400-485, WPR400, WRI400 data sheets for complete AD Series specifications.

System capabilities:

| | AD-400/401 | AD-300/301 | |
|--|----------------------------|----------------------------|--|
| | PIM400-485-VBB | Direct RS-485 | |
| Features | | | |
| Maximum number of readers supported by controller/PIM | 32 | 32 | |
| Maximum number of readers per PIM400 | 16 | N/A | |
| Maximum number of PIM400s and/or AD-300s per RS-485 Port | Up to 16 | Up to 16 | |
| Access control decision made by host or by lock database | Host | Host | |
| Readers - see supported card formats below | | | |
| Keypad only | Yes | Yes | |
| Magnetic stripe card | Yes | Yes | |
| Multi-technology - 125 kHz proximity | Yes | Yes | |
| and 13.56 MHz smart card | (up to 32 bits smart card) | (up to 32 bits smart card) | |
| PIV & PIV-I card compatible ¹ | No | Yes | |
| Card + PIN | Yes (up to 4 digit PIN) | Yes (up to 4 digit PIN) | |
| Status monitors | | | |
| Request to exit | Yes | Yes | |
| Door position | Yes | Yes | |
| Mechanical key override | Yes ³ | Yes ³ | |
| Request to enter | Yes | No | |
| Low battery status | Yes | N/A | |
| Communication status: RF/RS-485 | Yes/Yes | Yes | |
| Remote lockdown/unlock | Yes (<10 sec) ² | Yes | |
| Deadbolt position | Yes ^{2,3} | Yes ^{2, 3} | |
| Interior push button | Yes | Yes | |
| Lock functions | | | |
| Classroom/storeroom | Yes | Yes | |
| Office/toggle | Yes ^{2,3} | Yes ^{2, 3} | |
| Privacy | Yes ^{2,3} | Yes ^{2,3} | |
| Apartment | Yes ^{2,3} | Yes ^{2,3} | |

Please contact Vanderbilt Industries for additional details on integrated features and

Supported card formats

Proximity cards (125 kHz):

- AWID[®]
- GE/CASI[®]
- HID[®]
- Schlage[®]
- XceedID[®]

Smart cards (13.56 MHz):

- aptiQ[™] MIFARE Classic
- aptiQ[™] MIFARE DESFire[™] EV1
- PIV and PIV-I compatible¹
- Smart cards (13.56 MHz) reads card serial number only:
- HID iCLASS[®]
- DESFire[®]
- MIFARE[®]
- MIFARE DESFire[™] EV1
- 1 FIPS 201 compliant option available requires FMK reader: the ad-series can be used in applications which require approval by the US Federal government under HSPD-12 for FIPS 201 compliance. Specific components are required, please see the AD-401 and AD-301 data sheets for complete details. Contact Vanderbilt to confirm they are able to support your FIPS 201 credential format.
- 2 Requires RS-485 connection to bright blue controller.
- 3 Enhanced features that are only available in the upgraded versions of bright blue v2.1.1 or higher.

Available AD Series reader modules



Proximity

KEYPAD

Smart card

Multi-technology

FIPS 201-1 compliant

option available (FMK)



Proximity

Smart card



Magnetic stripe

(insertion)

KEYPAD







(swipe)

Cylindrical Lock

(AD-300/400)

KEYPAD

Magnetic stripe





(swipe)

Magnetic stripe



Keypad



Handheld device (HHD)

Used to initialize, configure, and test AD Series Devices

Compatibility

AD Series electronic locks from Schlage are built from the ground up to provide more options, more functionality and more compatibility than any other solution on the market today. Designed to suite with the most popular lever styles and finishes, Schlage AD Series locks can be configured to accept most major key systems.

Mortise Lock (AD-300/400)







Exit Device Trim





The AD Series exit trims are exclusively compatible with exit devices made by Allegion when using the low current request to exit switch (RX-LC part # 050281 for Von Duprin 98/99 & Von Duprin 22/22F Rim/SVR devices and part number 650359 for Falcon 25 Rim devices).

Cylinder compatibility

| Cylinder compatibility | Full size key-in-lever 6 pin | Full size key-in-lever 7 pin | FSIC 6 pin | SFIC 6 and 7 pin | _ |
|--------------------------------------|------------------------------------|------------------------------------|----------------|------------------------|---|
| Schlage | • | | • | • | _ |
| Falcon® | | | | | _ |
| Sargent® (10L + 11L full size) | | | | | = with cylinder or less cylinder options |
| Corbin Russwin [®] | | | ▲ ¹ | | e with cylinder of less cylinder options e less cylinder, only with Sparta and Rhodes levers |
| Yale® (includes Medeco 31*0100 FSIC) | | | | | = less cylinder only |
| Best [®] | | | | | I JDCO7 Corbin Russwin 7 pin cylinder is available in Rhodes, Sparta and Tubular |

Lever styles

Standard cylinders shown, SFIC and FSIC also available.





Athens



Tubular



Finishes Warm tone finishes



Allegion, the Allegion logo, Schlage, the Schlage logo, Von Duprin, Falcon, and aptiQ are trademarks of Allegion plc, its subsidiaries and/or affiliates in the United States and other countries. All other trademarks are the property of their respective owners.

About Allegion

Allegion (NYSE: ALLE) creates peace of mind by pioneering safety and security. As a \$2 billion provider of security solutions for homes and businesses, Allegion employs more than 7,800 people and sells products in more than 120 countries across the world. Allegion comprises 23 global brands, including strategic brands CISA®, Interflex®, LCN®, Schlage® and Von Duprin® For more, visit www.allegion.com.





© 2014 Allegion 005082, Rev. 03/14 www.allegion.com/us