

VON DUPRIN®

ALK

Alarm kit



## Overview

The ALK battery alarm kit is a simple yet effective way to deter unauthorized use of an opening. While the exit device is still a means of egress, the ALK kit contains an internal horn. When the touch bar is depressed, the horn sounds to provide an audible means of signaling that the opening has been violated. The alarm kit can be armed or disarmed by key. The horn is rated at 85 decibel.

The key switch uses a standard 1 1/4" (32mm) mortise cylinder with a straight cam (Schlage 20-001, B502-191 cam). The unit operates on one standard 9-volt alkaline battery.

Alarm kits are available with a choice of two switch kits, RX or LX. RX monitors the touchpad and is furnished standard. LX optional latch bolt monitoring is recommended for use with surface vertical rod exit devices or when alarm needs to sound from both the exit device and trim side of the door. Specify ALK-LX.

The ALK is available in two styles, 33A/99ALK, grooved cover and 35A/98ALK, smooth cover.

## Features and benefits

- 24VDC Input and External Inhibit standard
- External Inhibit provides remote arming and disarming
- Automatically re-arms with 1 1/2, 3 or 4 1/2 minute time delay upon request
- Horn emits intermittent low battery alert signal
- Includes 6" x 20" decal for application on door "EMERGENCY EXIT ONLY. ALARM WILL SOUND."

## 98/99 Series

### Minimum door openings

Device	3' (914mm) Length	4' (1219mm) Length
98/98-F/99/99-F	2' 10" (864mm)	3' 4" (1016mm)
9875/9875-F/9975/9975-F	2' 10" (864mm)	3' 4" (1016mm)
9827/9827-F/9927/9927-F	2' 10" (864mm)	3' 4" (1016mm)
9857/9857-F/9957/9957-F	2' 10" (864mm)	3' 4" (1016mm)
9847/9847-F/9947/9947-F	2' 9" (864mm)	3' 3" (991mm)
9848/9848-F/9948/9948-F	2' 9" (864mm)	3' 3" (991mm)
9849/9849-F/9949/9949-F	2' 9" (864mm)	3' 3" (991mm)
9849/9849-F/9949/9949-F	2' 9" (864mm)	3' 3" (991mm)

#### To order, specify:

- Standard - 98 ALK or 99 ALK
- Cylinder dogging - CD98 ALK or CD99 ALK
- Special center case dogging - SD98 ALK or SD99 ALK
- Auto reset - AR 1 ½, 3 or 4 ½

## 33A/35A Series

### Minimum door openings

Device	3' (914mm) Length	4' (1219mm) Length
33A/35A	2' 9" (838mm)	3' 3" (991mm)
3327A/3527A	2' 8" (813mm)	3' 2" (966mm)
3347A/3347A-F 3547A/3547A-F	2' 8" (813mm)	3' 2" (966mm)
3348A/3348A-F 3548A/3548A-F	2' 8" (813mm)	3' 2" (966mm)

#### To order, specify:

- Standard - 33A ALK or 35A ALK
- Cylinder dogging - CD33A ALK or CD35A ALK<sup>1</sup>
- Auto reset - ALK-AR3

- 1 When the ALK is used, standard dogging is removed. If cylinder dogging is required for 3' or 4' doors the ALK can be moved to the hinge side of the device and standard cylinder dogging can be added.

Allegion, the Allegion logo, Schlage, Von Duprin and the Von Duprin logo are trademarks of Allegion plc, its subsidiaries and/or affiliates in the United States and other countries. All other trademarks are the property of their respective owners.

## About Allegion

Allegion (NYSE: ALLE) creates peace of mind by pioneering safety and security. As a \$2 billion provider of security solutions for homes and businesses, Allegion employs more than 7,800 people and sells products in more than 120 countries across the world. Allegion comprises 23 global brands, including strategic brands CISA®, Interflex®, LCN®, Schlage® and Von Duprin®. For more, visit [www.allegion.com](http://www.allegion.com).

aptiQ ■ LCN ■ SCHLAGE ■ STEELCRAFT ■ VON DUPRIN



© 2014 Allegion  
010101, Rev. 03/14  
[www.allegion.com/us](http://www.allegion.com/us)