


Standard Door Opening Height		Cable Part Number		Min-Max opening heights by stile width		
Feet	Inches	Top	Bottom	Hollow Metal/ Wide-Stile Al. (greater than 3-3/4" stile width)	Medium-stile Al. (2-3/4" - 3-3/4")	Narrow-stile Al. (2-1/8" - 2-3/4")
6'8"	80"	49CABLE.1033	49CABLE.1038	77-1/2" - 80-1/2"	78-1/2" - 80-1/2"	79-1/2" - 80-1/2"
7'	84"	49CABLE.1034	49CABLE.1039	81-1/2" - 84-1/2"	82-1/2" - 84-1/2"	83-1/2" - 84-1/2"
7'2"	86"	49CABLE.1022	49CABLE.1040	83-1/2" - 86-1/2"	84-1/2" - 86-1/2"	85-1/2" - 86-1/2"
8'	96"	49CABLE.1035	49CABLE.1041	93-1/2" - 96-1/2"	94-1/2" - 96-1/2"	95-1/2" - 96-1/2"
9'	108"	49CABLE.1036	49CABLE.1042	105-1/2" - 108-1/2"	106-1/2" - 108-1/2"	107-1/2" - 108-1/2"
10'	120"	49CABLE.1037	49CABLE.1043	117-1/2" - 120 1/2"	118-1/2" - 120 1/2"	119-1/2" - 120 1/2"



Door Opening Height

is measured from finished floor to frame rabbet on door side.

Other Door Opening Heights up to 10'0" are available with extended lead time.

✓ Consult factory for lead time.