

Hospital Push/Pull Latches



6800 Series - Low Profile Cylindrical Latches

Innovation, Quality, Customer Service...


Standard Features

- Cylindrical latch application - passage function
- 1-3/4" standard door thickness (specify if different)
- Meets ADA requirements
- Trim is mounted using four thru-bolts for maximum stability
- Handing of unit is field-reversible by easily reversing the cam holder assembly on the backside of the unit
- Linear acting cam which provides for a smoother operating unit
- One continuous spring provides a smoother operation and an extended life for the unit
- UL Listed in U.S.A and Canada for use on door fire rated 90 minutes or less, up to 4'0" x 8'0"









Optional "Q" Quiet Latch available - Zero decibels gained when operating the handles.



Optional Round Cover & Custom Engraving Shown



Models

 6811	 6812	 6813	 6814	 6816	 6817	 6818	 6819
Push Down Pull Up Left Hand	Push Up Pull Down Left Hand	Push Up Pull Up Left Hand	Push Down Pull Down Left Hand	Push Down Pull Up Right Hand	Push Up Pull Down Right Hand	Push Up Pull Up Right Hand	Push Down Pull Down Right Hand

How to Order:

Example: 6811 - 2 A - US32D - AM

Model:

- 6811 • 6812 • 6813 • 6814
- 6816 • 6817 • 6818 • 6819

Latch Backset:

- 2 = 2-3/4" • 5 = 5"
- 3 = 3-3/4" • 7 = 7"

Strike:

- T = 2-3/4" T-Strike
- A = 4-7/8" ASA Strike

Finish:

- US32D • US32 • US10B • US3
- US26D • US26 • US10 • US4

Options, if Needed:

- H • AM • L • PL • PS • EX • X
- RC • SEC • THICK • P • Q

(See page C-3 to C-5 for details)



Architectural Builders Hardware Manufacturing, Inc.
1222 Ardmore Avenue, Itasca, IL 60143
Tel: 630-875-9900 • Fax: 630-875-9918 / 800-932-9224
Web: www.abhmfg.com • Email: abhinfo@abhmfg.com