

**Extra heavy-duty and heavy-duty overhead door holder/stop for exterior, vestibule and interior doors, single acting**

**Now available  
US32D & US32**

**8000 SERIES  
SURFACE MOUNTED**



**STANDARD FEATURES**

- Non-handed/reversible
- Single point hold-open in increments of 5° from 85° to 110°
- Hold-open holder shall engage and release door automatically by brass/stainless steel handle, or act as a stop only
- Maximum opening 110°, minimum door thickness 1 1/4"
- Wood, machine screws and sex bolts included
- Available in all BHMA finishes
- For extra heavy duty add **HD** before holder number. Four sex bolts provided for the door portion.

**All Stops  
Warnock Hersey  
listed**

**WHEN ORDERING,  
please list:**

*Model number*

*Door closer number or other hardware*

*Mounting means of the door and butt size*

*Hold-open or dead-stop degree*

*Door opening and thickness*

*Finish*

**SPECIFICATIONS:**

**Stop only function to be Warnock Hersey listed as manufactured by ABH.**

*Material:  
Housing 1/8" thick; arm 1/4" thick and 1" wide; jamb bracket 1/4" thick and 1" wide. Hold-open mechanism-stop PIN #303 stn. steel; lock plate case harden .0101 to .012 deep.*

DOOR FRAME OPENING		HOLDER NUMBER	
BUTTS OFFSET PIVOTS	CENTER HUNG	HOLD-OPEN	STOP
27" - 32 7/16"	29 1/2" - 34 15/16"	8010	8020
32 1/2" - 38 11/16"	35" - 41 7/16"	8011	8021
38 3/4" - 42 7/16"	41 1/2" - 44 15/16"	8012	8022
42 1/2" + Greater	45" + Greater	8013	8023
BHMA NUMBER		C03511	C03541
FED. SPEC TYPE		GJ80	GJ80

Contact ABH for special templating or other door opening  
Average weight/unit 4 1/2 lbs.

**www.abhmfg.com**  
**E-mail: abhinfo@abhmfg.com**  
**Architectural Builders Hardware Mfg., Inc.**  
 1222 Ardmore Ave., Itasca, IL 60143  
**630.875.9900; FAX 800.9FAXABH (932.9224)**

© 2005 ABH Mfg., Inc.  
Printed in USA 02/05

