

# MODEL SLP-1M

## MONITORING/CONTROL STATION



### SPECIFICATIONS

- DESIGNED TO RELEASE OR SECURE AND MONITOR ONE ELECTRIC LOCK
- ONE 1/2" RED LED OPERATES ON 12 OR 24 VOLTS AC OR DC
- ONE D.P.D.T. ILLUMINATED MOMENTARY PUSHBUTTON WITH HI-BRIGHTNESS BUILT-IN LED
- SWITCH LED OPERATES ON 12 OR 24 VOLTS AC OR DC
- SWITCH CONTACTS RATED 3 AMPS @ 35 VDC OR 120 VAC
- COMPONENTS MOUNTED ON STANDARD SINGLE GANG ELECTRICAL WALLPLATE
- SWITCH AND LED TERMINATED WITH COLORED LEADS
- GREEN AND YELLOW LEDS ARE AVAILABLE
- CUSTOM SWITCH LEGENDS ARE AVAILABLE
- ORDER MODEL SLP-1L FOR SWITCH WITH LATCHING CONTACTS



**ALARM CONTROLS CORPORATION**

19 BRANDYWINE DRIVE P.O. BOX 280

DEER PARK, NY 11729

1 631 586-4220 1 800 645-5538

WWW.ALARMCONTROLS.COM EMAIL INFO@ALARMCONTROLS.COM

## **SLP WIRING INSTRUCTIONS**

### **SWITCH LED**

OPERATES ON 12 OR 24 VOLTS  
AC OR DC

|                    |                 |
|--------------------|-----------------|
| <b>YELLOW LEAD</b> | <b>POSITIVE</b> |
| <b>BLACK LEAD</b>  | <b>NEGATIVE</b> |

### **SWITCH**

|                   |                    |
|-------------------|--------------------|
| <b>RED LEAD</b>   | <b>N/C CONTACT</b> |
| <b>BLUE LEAD</b>  | <b>N/O CONTACT</b> |
| <b>WHITE LEAD</b> | <b>COM CONTACT</b> |

### **LED**

FOR 12 VOLT OPERATION

|                   |                 |
|-------------------|-----------------|
| <b>WHITE LEAD</b> | <b>POSITIVE</b> |
| <b>BLACK LEAD</b> | <b>NEGATIVE</b> |

FOR 24 VOLT OPERATION

|                   |                 |
|-------------------|-----------------|
| <b>RED LEAD</b>   | <b>POSITIVE</b> |
| <b>BLACK LEAD</b> | <b>NEGATIVE</b> |



**ALARM CONTROLS CORPORATION**