

# MODEL TS-55R

## MONITORING/CONTROL STATION



### SPECIFICATIONS

- DESIGNED TO RELEASE OR SECURE AND MONITOR ELECTRIC LOCKS
- 1/2" RED LED OPERATE ON 12 OR 24 VOLTS AC OR DC
- 1-1/2" DIA. RED ILLUMINATED MOMENTARY PUSHBUTTON WITH HI- BRIGHTNESS BUILT-IN LED
- PUSHBUTTON LED OPERATES ON 12 OR 24 VOLTS AC OR DC
- ONE N/O AND ONE N/C CONTACT RATED 10 AMPS @ 35 VDC OR 120 VAC
- COMPONENTS MOUNTED ON STANDARD SINGLE GANG ELECTRICAL WALLPLATE
- WEATHERPROOF RATED TO IP65, NEMA TYPE 4
- ORDER MODEL TS-56R FOR LATCHING CONTACTS



**ALARM CONTROLS CORPORATION**

19 BRANDYWINE DRIVE P.O. BOX 280  
DEER PARK, NY 11729

1 631 586-4220 1 800 645-5538

WWW.ALARMCONTROLS.COM EMAIL INFO@ALARMCONTROLS.COM

## **LED WIRING INSTRUCTIONS**

FOR 12 VOLT OPERATION

**WHITE LEAD      POSITIVE**

**BLACK LEAD      NEGATIVE**

FOR 24 VOLT OPERATION

**RED LEAD      POSITIVE**

**BLACK LEAD      NEGATIVE**

