



K200 Series Cabinet Lock

Works with cabinet doors and lockers up to 1-1/2" thickness

Easily
Extend
Wiegand
Access
Control to
Cabinets
and
Drawers

Secure

High Security Asset Protection

Single credential solution to meet compliance and safety regulations

Enables real-time audit capabilities and door monitoring

Mechanical key override capability

Convenient

Easy Installation

Flexible design

Suitable for wood or metal cabinet applications

Non-handed

Versatile

Multi-Technology Reader

Complete upgrade solution that supports both Prox and iCLASS credentials

Uses Wiegand communication

Integrates with existing access control systems and ID badges



K200 Series Cabinet Lock

Features

Standard Features

- Multi-technology reader
- Integrates with existing access control systems
- Hard wired Wiegand communication
- Mechanical key override capable (cam lock not included)
- Static strength 150 lbs
- Latchbolt status monitoring
- Dual voltage 12 or 24 VDC
- Non-handed

- Installs on wood or metal cabinet doors
- Works with cabinet doors and lockers up to 1-1/2" thickness
- Three year limited warranty

Accessories

CABLEW10-8 » Wiegand wire 8 ft extension, 10 conductor with Molex connectors

Finishes

- Black

Specifications

Listings and Patents

- FCC Part 15 & Industry Canada Compliant
- EU/CE Mark (EN 300 & 301)
- RoHS Compliant
- ANSI A156.11 2003 Grade 1
- Operating Temperature +32 to +122F [0 to +50C]
- Credentials supported: 125kHz Prox or 13.56 MHz; iCLASS®, iCLASS Elite, iCLASS SEOS™, iCLASS SE, ISO 15693 iCLASS, ISO 14443A Mifare, Mifare Plus, Desfire SE, Desfire EV1, HCE over NFC
- Patents pending

Door Application

- Metal
- Wood

Electrical (continuous duty)

- 12 - 24 VDC +/- 10%
- 226 mA peak at 12 VDC
- 118 mA peak at 24 VDC

