440 Heavy Duty Series Exit Switches

The conspicuous 440 Heavy Duty Industrial Series switch assemblies incorporates a 2 5/8" inch diameter mushroom button and heavy duty weather resistant contacts. The large 2 gang mushroom assembly includes a heavy duty steel bezel around the button to guard against abuse. When utilized as an Exit or REX switch, the assembly is easy to activate and stands out for persons without prior knowledge of egress operation.

In addition to egress applications, the large assembly is ideal as an easy to activate Emergency/Panic Alarm Switch.



440



MODELS

3	MODELS 1 GANG 446U	Momentary DPST	FXIT
	2 GANG		
	441U	AA (On/Off) DPST	None
	442U	Momentary DPST	EXIT
	443U	Momentary with Electronic Timer Module, Adj., 1-60 sec, 12/24V AC/DC, SPDT 2A Contact	EXIT
	444U	Momentary 2-DPST	EXIT





FEATURES

- 2-5/8" Mushroom Exit & Panic Switches
- Heavy Duty Steel Bezel to Guard Against Abuse
- Water Resistant Contacts
- Easy to Activate Emergency & Panic Switch
- Dull Stainless Steel Finish
- Red Button Standard
 Specify G for Green Button

SPECIFICATIONS

Button	Mushroom, 2 5/8"
Contact	6 Amp @ 30VDC Resistive
Wire Connection	Screw Terminals
1 Gang	2 7/8" x 4 1/2" x 20 Ga.
2 Gang	4 1/2" x 4 1/2" x 20 Ga.
Timer Input	12/24 VDC / VAC @ 50 mA
Timer Trigger Input	N.O. Dry
Timer Contact	SPDT Dry, 2 Amps @ 30VDC
Timer Wire Leads	6", 20 Gauge
Timer Size	3/4" x 1-1/2" x 2-1/4"
Weight	0.5 lbs



LIT-440 SERIES SWITCHES 01/17