

450 Vandal Resistant Series

Exit Switches

The **SDC 450 Series** incorporates a 1/4" thick aluminum faceplate and an all stainless steel button. The assembly will resist the impact of a hammer blow. In addition, security spanner mounting screws are concealed by tamper resistant aluminum plugs to inhibit tampering.

PNEUMATIC TIME DELAY

The 453P includes a 1 to 180 second pneumatic timer for delayed re-locking. Where preferred, the 10TD Electronic Mini Timer may be specified for use with the standard 452 model.



450



450N



FEATURES

- Stainless Steel Button - 1/4" Thick Aluminum Plate
- Security Screws



SPECIFICATIONS

Button	Round Dull Stainless Steel button, 1/2"
Contact	6 Amp @ 30VDC Resistive
Wire Connection	451/452: 6", 20 Gauge 453P: Screw terminals
1 Gang	2 7/8" x 4 1/2" x 1/4"
Narrow	1 3/4" x 4 1/2" x 1/4"
Weight	0.5 lbs



MODELS

1 GANG

451V AA (On/Off) SPDT



452V Momentary SPDT

453PV Integrated Pneumatic Timer
Adj. 1-180 sec. DPST Contact

NARROW SERIES

451NV AA (On/Off) SPDT



452NV Momentary SPDT

453PNV Integrated Pneumatic Timer
Adj. 1-180 sec. DPST Contact



