

EntryCheck™ Series Digital Keypads

SDC DESIGNED AND MANUFACTURED

The SDC EntryCheck™ series consists of stand alone digital keypads designed to control access of a single entry point for facilities. Each user is assigned a personal identification number (PIN). Keypad entry of a valid one to six digit code activates one or both of the output relays which releases an electric door lock. Optional Prox Readers and Wiegand Output are available for select models



918 Series



920 Series



923 Series



Select models include Wiegand output

EntryCheck™ multi-piece options:



921P & 924P



925 Series




920

Indoor/Outdoor
Stand-Alone Keypad,
Surface Mount
3"W x 5-3/4"H x 1-7/16"D
(1.5" wall projection)



920P

Indoor/Outdoor
Stand-Alone Keypad
with Prox Reader
3"W x 5-3/4"H x 1-7/16"D
(1.5" wall projection)



921P

Indoor/Outdoor Keypad,
2 piece Configuration:
Keypad and Controller,
Surface Mount
Keypad Dimensions:
3"W x 5-3/4"H x 1-7/16"D
(1.5" wall projection)



923

Indoor/Outdoor
Stand-Alone Narrow Keypad,
Surface Mount
1-3/4"W x 7-5/16"H x 1-3/8"D
(1.5" wall projection)



923P

Indoor/Outdoor
Stand-Alone Narrow Keypad
with Prox Reader
1-3/4"W x 7-5/16"H x 1-3/8"D
(1.5" wall projection)



924P

Indoor/Outdoor Keypad,
2 piece Configuration:
Keypad and Controller,
Surface Mount
Keypad Dimensions:
1-3/4"W x 7-5/16"H x 1-3/8"D
(1.5" wall projection)

FEATURES

- Weather Resistant
- Heavy Cast Vandal Resistant Housing
- Heavy Cast Metal Blue Backlit Keys
- Keypad programmable
- 500 Users, 1-6 digit PIN codes
- 4 Outputs, 2 relay and 2 solid state outputs timed or latching (on/off)
- Assign entry PIN's to relays 1 and/or 2
- LED Status: Access, lockout
- Tactile keys with selectable audible levels for key depression or output activation
- Timed anti-passback, anti-tailgate
- Keypad tamper lockout
- Request-to-Exit/Enter input
- Choice of door sense/relay inhibit input functions; Forced Entry, Door Ajar, or Inhibit Relay 1 or 2, Auto Relock When Door Closes
- Choice of 2 solid state outputs functions; Alarm Shunt, Forced Entry, Door Ajar, Tamper lockout or Keypad Active

PROX ONLY:

- 3 User Modes:
- PIN or Card
 - Card Only
 - Card and PIN
 - HID-Compatible (125kHz-RFID)



KEYPAD SPECIFICATIONS

Voltage	12/24 VAC/DC
Current	30mA typical, 150mA maximum
Outputs	Relay 1 - SPDT 5 Amps @ 30VDC Relay 2 - SPDT 2 Amps @ 30VDC Switch to Common Outputs 3 & 4 - 100mA @ 30VDC
Temperature	-22°F to + 149°F (-30°C to + 65°C)
Humidity	5% to 95% non-condensing
Finish	Powder Coat Painted Cast Metal

***ACCESSORIES - ACCESS CREDENTIALS**

HID1326-25	HID ProxCard® II, 25 cards
HID1326-100	HID ProxCard® II, 100 cards
HID1346-10	HID ProxKey® II, 10 key fobs
HID1346-100	HID ProxKey® II, 100 key fobs

*Prox Reader Accessories



EntryCheck™ Heavy Duty Keypads with Wiegand Output



918W
Indoor Keypad
Wiegand Output
Single Gang
3"W x 4-3/4"H x 1"D
(1/4" wall projection)

FEATURES

- Digital Keypad with Wiegand Output for Universal Compatibility
- 12-Key Illuminated, Moisture-Resistant 3 x 4 Keypad
- Tamper-Resistant Screws
- Single-Gang Mount
- Programmable Site Code
- Dual LED Status Indicators
- Adjustable Audible Annunciation
- Configurable Illumination: On, Off, Timed

918W SPECIFICATIONS

Keypad	Brushed stainless steel 3/32" (2mm) thick
Voltage	5-16VDC
Current	25mA typical, 40mA max.
Keypad Output	26-bit Wiegand
Wiring	6" Pigtail
Temperature	-10°F to +130°F (-23°C to +54°C)
Humidity	5% to 95% Non-Condensing



920PW
Indoor/Outdoor
Wiegand Keypad
with Prox Reader
3"W x 5-3/4"H x
1-7/16"D
(1.5" wall projection)



923PW
Indoor/Outdoor
Wiegand Narrow Keypad
with Prox Reader
1-3/4"W x 7-5/16"H x 1-3/8"D
(1.5" wall projection)



925PW
Indoor/Outdoor
Wiegand Keypad
with Prox Reader
and Privacy
Shroud
4-1/16"W x 6-1/8"H
x 2-5/8"D
(shroud dimension)



FEATURES

- Digital Keypad with Wiegand Output for Universal Compatibility
- Weather & Vandal-Resistant Housing with Tactile Metal Keys
- HID-Compatible Proximity Reader
- 12-Key Illuminated Keypad
- Surface or Single-Gang Mount
- Built-In Tamper Switch
- Programmable Site Code
- Dual LED Status Indicators
- Adjustable Audible Annunciation
- Configurable Illumination: On, Off, Timed

920PW / 923PW / 925PW SPECIFICATIONS

Keypad Housing	Powder Coat Painted Cast Metal
Voltage	5-16VDC
Current	30mA typical, 60mA max.
Reader Output	26-bit Wiegand
Reader Frequency	125kHz
Keypad Output	26-bit Wiegand or 4-bit Word
Wiring	6" Pigtail
Temperature	-22°F to +149°F (-30°C to +65°C)
Humidity	5% to 95% Non-Condensing

* See page two for Prox Reader accessories



918

Indoor Stand-Alone Keypad
Single Gang
3"W x 4-3/4"H x 1-1/2"D
(1/4" wall projection)




FEATURES

- 500 Users, 1-6 digit PIN codes
- 4 Outputs, 2 relay and 2 solid state outputs timed or latching (on/off)
- Assign entry PIN's to relays 1 and/or 2
- LED Status: Access, lockout
- Tactile keys with selectable audible levels for key depression or output activation
- Timed anti-passback, anti-tailgate
- Keypad tamper lockout
- Request-to-Exit/Enter input
- Indoor blue backlit, moisture resistant keypad



918 SPECIFICATIONS

Voltage	12/24 VAC/DC
Current	30mA typical, 150mA maximum
Outputs	Relay 1 - SPDT 5 Amps @ 30VDC Relay 2 - SPDT 2 Amps @ 30VDC Switch to Common Outputs 3 & 4 - 100mA @ 30VDC
Temperature	-10°F to + 130°F (-23°C to + 54°C)
Humidity	5% to 95% non-condensing
Finish	Brushed Stainless Steel



925 Series
is perfect
for Post-Mount
Applications
(Post by others)



925

Indoor/Outdoor Keypad
with Privacy Shroud



925P

Indoor/Outdoor Keypad
with Privacy Shroud
and Prox Reader



FEATURES

- Weather Resistant
 - Heavy Cast Vandal Resistant Housing
 - Heavy Cast Metal Blue Backlit Keys
 - Keypad programmable
 - 500 Users, 1-6 digit PIN codes
 - 4 Outputs, 2 relay and 2 solid state outputs timed or latching (on/off)
 - Assign entry PIN's to relays 1 and/or 2
 - LED Status: Access, lockout
 - Tactile keys with selectable audible levels for key depression or output activation
 - Timed anti-passback, anti-tailgate
 - Keypad tamper lockout
 - Request-to-Exit/Enter input
 - Choice of door sense/relay inhibit input functions; Forced Entry, Door Ajar, or Inhibit Relay 1 or 2, Auto Relock When Door Closes
 - Choice of 2 solid state outputs functions; Alarm Shunt, Forced Entry, Door Ajar, Tamper lockout or Keypad Active
- PROX ONLY:**
3 User Modes:
- PIN or Card
 - Card Only
 - Card and PIN
 - HID-Compatible (125kHz-RFID)



925 / 925P SPECIFICATIONS

Voltage	12/24 VAC/DC
Current	30mA typical, 150mA maximum
Outputs	Relay 1 - SPDT 5 Amps @ 30VDC Relay 2 - SPDT 2 Amps @ 30VDC Switch to Common Outputs 3 & 4 - 100mA @ 30VDC
Temperature	-22°F to + 149°F (-30°C to + 65°C)
Humidity	5% to 95% non-condensing
Finish	Powder Coat Painted Cast Metal

See page two for Prox Reader accessories

