



FEATURES

- Public, Private & Remote Allocation System (RAS) mode
- Fits most standard metal lockers "out of the box"
- Simple click together fit, with 2 nuts to secure
- Designed to work with locking bar lifter
- ADA compliant as standard
- Key override
- Up to 80,000 operations per pair of batteries (included)
- Battery condition indicator
- Audible key press (can be turned on/off)
- Re-lock indicator
- 4 digit user code (can be set by user)
- 8 digit master code
- 6 digit technician code

OPTIONS

- Finishes: Silver (S), Black (B), Custom (C)*
- Remote Allocation System (RAS)

DIMENSIONS & SPECIFICATIONS

External Dimensions:

- Length: 73.5mm (2.9in)
- Width: 52mm (2.05in)
- Depth: 28mm (1.1in)

Internal Dimensions:

- Length: 67.5mm (2.66in)
- Width: 93mm (3.66in)
- Depth: 22.4mm (.88in)

Power: 2 x AA Battery (Alkaline)

Operations: Up to 80,000 cycles per pair of AA batteries

Low Battery: LED indicator lights with battery condition indicator


Material: Heavy duty zinc die-cast construction

Finish: Powder coated

For Internal Use

ORDERING INFORMATION

Order # for EC-790 shown above is EC-790S

PART #	FINISH	REMOTE ALLOCATION SYSTEM
EC-790	(S) SILVER (B) BLACK (C) CUSTOM*	(RAS) 

*Contact LockeyUSA for minimum order quantities and lead times for special/custom orders.

