

9849/9949 Concealed Vertical Cable Device

VON DUPRIN.



Hex key dogging comes standard on 9849/9949 Concealed Vertical Cable Devices

9849/9949 concealed vertical cable device for use on single or metal doors, UL listed for Panic Exit Hardware. Devices are ANSI A156.3 – 2001 Grade 1. The 9849 device has a smooth mechanism case and the 9949 device has a grooved case. The concealed vertical cable device is non-handed except when the following device options are used: SD (Special Dogging), or SS (Signal Switch). See Opposite page for available outside trim and device functions.

Finishes – US3, US3A, US4, US4A, US10, US15, US26, US26D, US26D-AM Antimicrobial, US28, 313, 315 & 643E. US32D available with 98 Series only.



Specifications

Device Functions	Device ships EO/DT/NL. Field selectable. For TP, K or L remove NL drive screw from device.
Device Lengths	2' 2' (610mm) Door Size 3' 2'4" to 3' (711mm to 914 mm) Door Size 4' 2'10" to 4' (864 mm to 1219 mm) Door Size
Device Centerline from Finished Floor	39 5/8" (1006 mm) Standard
Center Case Dimensions	8" x 2 3/4" x 2 3/8" (203mm x 70mm x 60mm)
Mechanism Case Dimensions	2 1/4" x 2 1/4" (57mm x 57mm)
Projection	Pushbar Neutral – 3 13/16" (97 mm) Pushbar Depressed – 3 1/16" (78 mm)
Latch Bolt	Deadlocking Top & Bottom Bolt, 1/2" (13mm) throw
Door Undercut	3/4" (19mm) maximum
Top & Bottom Latch Case	5 13/16" x 1 1/4" x 1 7/16" (147mm x 32mm x 37mm)
Vertical Cable	7/32" (6mm) Diameter Stainless Steel Cables
Fasteners & Sex Bolts (SNB)	Includes screw pack for 1 3/4" (44mm) and 2 1/4" (57mm) thick metal doors. Optional 425 SNB available.
Electric Options	ALK Alarm Exit Kit CX Chexit Delayed Exit E Electric Unlocking and Locking Trim EL Electric Latch Retraction HD-EL Electric Latch Retraction w/ Hex Dogging LX Latchbolt Monitor Switch QEL Quiet Electric Latch Retraction RX2 Double Pushpad Monitor Switch RX996L Trim Monitor Switch RX Pushpad Monitor Switch RXLC Pushpad Monitor Switch - Low Current SS Signal Switch WP-RX Waterproof Request to Exit
Mechanical Options	GBK Glass Bead Kit LBL Less Bottom Latch PN Pneumatic Latch Retraction SEC Security Screws SG Safety Glow SLM SLM Blocking SNB Sex Bolts
Dogging Feature Dogging Options	Hex key dogging standard CD Cylinder Dogging LD Less Dogging SD Special Center Case Dogging DI Dogging Indicator CDI Cylinder Dogging Indicator
Strikes	Top - 249 - Unfinished, Bottom - 349 - Unfinished

QEL

Quiet Electric Latch Retraction

- Bolt retraction via switch
- Converts exit door to push-pull operation

CD

Cylinder Dogging

- Replaces hex key dogging
- Requires standard 1 1/4" mortise cylinder

CX

Chexit Delayed Exit

- Meets NFPA 101 requirements
- Self-contained controls, locking, alarm

RX

Pushpad Monitor Switch

- Signals use of an opening
- SPDT switch to monitor pushpad

EL

Electric Latch Retraction

- Enables remote unlatching
- Alternative to manual dogging

ALK

Alarm Exit Kit

- Unauthorized opening triggers 85-decibel horn
- Set in armed or disarmed mode by key

PN

Pneumatic Latch Retraction

- For areas where electrical devices banned
- Special linkage for mechanical or pneumatic dogging

DI

Dogging Indicator

- Monitor dogging status without a control panel
- Red indicator light shows visibility to dogging from over 75 feet

E (E 996L)

Electrified Breakaway Lever




- Electrified remote locking/unlocking
- Standard in fail safe condition





SG

Safety Glow

- Self illuminating touchpad
- No batteries or electronics


Standard Trim


	EO	DT	NL	NL-OP
				
	Exit only	Dummy Trim Pull When Dogged	Night Latch Key Retracts Latchbolt	Night Latch Key Retracts Latchbolt Optional Pull Required
Product Description	9849EO 9949EO	9849DT 9949DT	9849NL 9949NL	9849NL-OP 9949NL-OP
Trim Description	—	990DT	990NL-R/V	110NL-MD
Escutcheon Plate Size	—	3" x 14 ³ / ₁₆ " x ³ / ₃₂ " (76x360x2mm)	3" x 14 ³ / ₁₆ " x ³ / ₃₂ " (76x360x2mm)	—
Pull Center to Center	—	5 ¹ / ₂ " (140mm)	5 ¹ / ₂ " (140mm)	—
Projection	—	2" (51mm)	2" (51mm)	—
ANSI Function	01	02	03	03
Cylinder Type	—	—	Rim	Rim
Handing	—	—	—	—
Optional Trim <i>see pages 44-46</i>	x990EO x996EO	x996K-DT x996L-DT x697DT	x996K-NL x996L-NL x697NL	
Quantity needed Optional 425 SNB	6	2	2	6


	L	L-NL	L-BE	L-DT
				
	Lever Key Locks & Unlocks	Lever - Night Latch Key Retracts Latchbolt	Lever - Blank Escutcheon Always operable (No Cylinder)	Lever Dummy Trim Pull When Dogged
Product Description	9849L 9949L	9849L-NL 9949L-NL	9849L-BE 9959L-BE	9849L-DT 9949 L-DT
Trim Description	996L-R/V*	996L-NL-R/V	996L-BE-R/V*	996L-DT
Escutcheon Plate Size	2 ³ / ₄ " X 10 ³ / ₄ " X ²⁷ / ₃₂ " (70x273x21mm)	2 ³ / ₄ " X 10 ³ / ₄ " X ²⁷ / ₃₂ " (70x273x21mm)	2 ³ / ₄ " X 10 ³ / ₄ " X ²⁷ / ₃₂ " (70x273x21mm)	2 ³ / ₄ " X 10 ³ / ₄ " X ²⁷ / ₃₂ " (70x273x21mm)
Pull Center to Center	—	—	—	—
Projection	2 ⁷ / ₈ " (73mm)	2 ⁷ / ₈ " (73mm)	2 ⁷ / ₈ " (73mm)	2 ⁷ / ₈ " (73mm)
ANSI Function	08	03	14	02
Cylinder Type	Rim	Rim	—	—
Handing	Handed/Reversible	Handed/Reversible	Handed/Reversible	Handed/Reversible
Quantity needed Optional 425 SNB	2	2	2	2

* Electrified lever operation available.

Optional Trim


Knobs


Thumbpieces


Lever Designs

Standard Door Height	
Feet	Inches
6'8"	80"
7'	84"
8'	96"
9'	108"
10'	120"

Note:

Non-standard sizes available with extended lead time.
 Consult Customer Care for more information 1-877-671-7011.

9849/9949 Concealed Vertical Cable Device