


400 Series

Wireless Transmitter & Receiver



**433MHz 1 Channel
Micro Transmitter**

For Remote Control Versatility for Touch Panel Column and Push Plate Switches. 75 foot wireless range. less barriers.



**433MHz 1 Channel
Nano Receiver**

Designed to control automatic door or electrified locking hardware with code-hopping technology for increased security.



FEATURES

- Requires a Non-Metallic Surface Box or Standard Bollard Cap (non-metallic)
- Pre-Wired for Quick Installation
- Antenna Magnifies Signal
- Works with 400RC433



MODELS



400W1-433 433MHz Micro Transmitter



FEATURES

- Designed to Control Automatic Closing and Anti-Burgular Systems
- Works with 400W1-433



MODELS



400RC433 433MHz One Channel Receiver



SPECIFICATIONS

Voltage Input	9V Battery (included)
Trigger Input	Momentary, N.O.Dry Contact
Temperature	-20°F — 100°F
Dimensions	1-9/64" x 15/16" x 7/32"



SPECIFICATIONS

Carrier Frequency	433.92 MHz
Power Supply	12/24 VAC/DC (Jumper select)
Relay Numbers	1
Contacts	C-NO
Temperature	-4°F — 158°F
Dimensions	1-1/4" x 2" x 3/4" Deep

