



ACCESS  
HARDWARE  
SUPPLY

# SimpleSwing Low Energy Operators By Record

Don't let the name fool you. The SimpleSwing has a LOT going on – so much that it meets or beats all of the competition – on all fronts.

The SimpleSwing is a low energy door operator that can accommodate most types of doors, and a built-in SimpleLynk programing display panel makes the system simple to setup and program. With its robust features set and a 3 year warranty, the SimpleSwing is scaring the competition. (See comparison chart on other side)

**Perfect for libraries, healthcare facilities, universities, storefronts and more...**



Visit [accesshardware.com/manufacturers-m-r/record/](http://accesshardware.com/manufacturers-m-r/record/) to learn more and to download SimpleSwing specification and installation sheets.

Questions? Call **855.847.5691** to speak to one of our hardware pros. Remember, for knowledge, service and inventory – you can't beat AHS.

## KNOWLEDGE. SERVICE. INVENTORY.



ACCESS  
HARDWARE  
SUPPLY

DISTRIBUTED BY



ACCESS HARDWARE SUPPLY  
[accesshardware.com](http://accesshardware.com)



Now In Stock

## FEATURES



- Surface applied
- Right hand or left hand doors
- In-swinging or out-swinging doors
- Single, pairs or double egress doors
- Doors that require 120° door swing
- Swing clear doors
- For interior and exterior doors
- Up to 750 pounds per door leaf
- 28" doors through 96" door openings
- Meets ANSI A 156.19 Low Energy Door Fire rated openings (UL 228)
- Clear aluminum and dark bronze anodized finishes
- ADA applications
- Push to start applications – no need for additional activation
- Simplelynk Display

14447 Griffith Street, San Leandro, CA 94577

Phone 855.847.5691 • Fax 800.435.8233

[accesshardware.com](http://accesshardware.com)

# Comparison Chart

General Features	SimpleSwing	LCN AE	LCN SR Swing	Dorma ED400	Norton LEO
Opening Force <15lbs	✓	✓	✓	✓	✓
Opening Force <8lbs	✓	✓	✓	✓	✓
Adjustable opening speeds	✓	✓	✓	✓	✗
48" Single door	✓	✓	✓	✓	✓
Handed	✓	✗	✓	✗	✗
Push or pull operation	✓	✗	✓	✓	✓
Maximum door weight 750lbs	✓	✗	✗	✗	✗
High frequency use	✓	✓	✓	✓	✗
Complies wih ANSI 156.19	✓	✓	✓	✓	✓
Electro-mechanical	✓	✗	✓	✓	✗
Exterior/interior application	✓	✓	✓	✓	✓
Surface applied	✓	✓	✓	✓	✓
Full length header	✓	✗	✓	✓	✗
Push to start	✓	✗	✓	✓	✗
Auto-reverse	✓	✗	✓	✓	✓
Obstruction stop	✓	✓	✓	✓	✓
Stack pressure feature	✓	✗	✗	✓	✗
Microprocessor controlled	✓	✓	✓	✓	✗
Latch assist	✓	✓	✓	✓	✗
Adjustable latch check speed	✓	✓	✓	✓	✓
Programmable controls	✓	✓	✓	✓	✗
Positive stop	✓	✗	✓	✓	✗
Built-in electric strike interface	✓	✓	✗	✓	✗
Built-in interface for presence sensor	✓	✗	✗	✓	✗
Painted finishes	✓	✓	✓	✓	✓
Clad covers	✓	✓	✓	✓	✗
UL325	✓	✓	✓	✓	✓
UL228	✓	✓	✓	✓	✓
Self diagnostic	✓	✓	✗	✓	✓
3 year warranty	✓	✗	✗	✗	✗
2 year warranty	N/A	✓	✓	✗	✗

## KNOWLEDGE. SERVICE. INVENTORY.