



Model 9500



# 9500 Series

## Surface Mounted Electric Strike

Works with rim exit devices with a 3/4" throw latchbolt

### Safety

#### Enhanced Performance

UL 10C fire-rated, 3 hour (fail secure only)

UL 1034 burglary-resistant listed and suitable for outdoor use

ANSI/BHMA A156.31, Grade 1

### Convenient

#### Easy Installation

Completely surface mounted for quick installation

Base and cover are separate for easy adjustments

Field selectable fail safe/fail secure

### Durable

#### Proven Performance

Accommodates flexible frames

Suitable for metal or wood frame applications

Internal earth magnets prevent solenoid failure

The Strong & Durable, Fire-Rated, Surface Mounted Solution

ASSA ABLOY, the global leader in door opening solutions

[hesinnovations.com](http://hesinnovations.com)



RIM EXIT DEVICES



FIELD SELECTABLE  
(12 OR 24VDC)



FIELD SELECTABLE  
(FAIL SECURE / FAIL SAFE)



FIRE RATED



GRADE 1



OUTDOOR RATED



UL 1034  
BURGLARY LISTED



# 9500 Series

## Surface Mounted Electric Strike

### Features

#### Standard Features

- Installs in metal or wood frames
- Separate base and decorative cover for easy adjustments
- Stainless steel construction
- Static strength to 1,500 lbs.
- Dynamic strength to 70 ft-lbs.
- Endurance 1,000,000 cycles
- Field selectable fail secure/fail safe
- Dual voltage 12 or 24VDC
- Non-handed. Horizontal adjustability
- Five year limited warranty

#### Optional Features

- LBM** » Latchbolt monitor
- LBSM** » Latchbolt strike monitor

#### Accessories

- 9400/9500/9600-108** » Spacer plate (black or 630 finish)
- SMB** » Surface mounting box
- 2001M** » Plug-in bridge rectifier
- 2004M** » ElectroLynx® adapter
- 2005M3** » SMART Pac® III
- 2006M** » Plug-in buzzer

#### Finishes

- 630** » Satin stainless steel
- 605** » Bright brass
- 606** » Satin brass
- 612** » Satin bronze
- 613** » Bronze toned
- 629** » Bright stainless steel

### Specifications

#### Listings and Patents

- UL 10C fire-rated, 3 hour (fail secure only)
- CAN4-S104 (ULC-S104), NFPA-252 and ASTM-E152 fire door conformant
- UL 1034, burglary-resistant listed and suitable for outdoor use
- UL 294 (6th edition) listed
- ANSI/BHMA A156.31, Grade 1
- California Fire Marshall listed
- NFPA 80-07 compliant
- RoHS compliant
- Patent: 6,390,520

#### Frame Application

- Metal
- Wood

#### Electrical (continuous duty)

- .45 Amps @ 12 VDC
- .26 Amps @ 24VDC
- PoE friendly

