



These electric strikes are used with cylindrical locks, mortise locks\* and mortise exit devices



fire rated



UL 1034  
burglary listed



grade 1

## Applications

### 712

For hollow-metal frame applications - when the lockset has a 1/2" or 5/8" throw latchbolt

- 1/2" keeper standard

### 712-75

For hollow-metal frame applications - when the lockset has a 1/2" 5/8", or 3/4" throw latchbolt

- 3/4" keeper standard

### 732

For wood frame applications - when the lockset has a 1/2" or 5/8" throw latchbolt. Features an offset solenoid

- 1/2" keeper standard

### 732-75

For wood frame applications - when the lockset has a 1/2", 5/8", or 3/4" throw latchbolt. Features an offset solenoid

- 3/4" keeper standard

\*Note: These products will require relocation of the center line when used with mortise locks. Consult HES customer support regarding use with Best 40 Series.



The logo for Folger Adam, featuring the name in a white, serif font against a dark blue background with a grid pattern.

# Folger Adam®

The logo for hes ASSA ABLOY, featuring the word 'hes' in white lowercase letters on a green square background, with 'ASSA ABLOY' in white uppercase letters below it.

hes®  
ASSA ABLOY

## Specifications

- UL 10C, 3 hour single door fire-rated (fail secure only)
- UL 10C, 3 hour double door fire-rated (fail secure only)
- CAN4-S104 (ULC-S104) fire door conformant
- UL1034, burglary-resistant listed
- ANSI/BHMA A156.31, Grade 1
- DOD approved
- New York City accepted
- NFPA-252 fire door conformant
- ASTM-E152 fire door conformant

## Electrical

- .29 Amps @ 12VDC continuous duty
- .15 Amps @ 24VDC continuous duty

## Standard Features

- Tamper resistant, heavy-duty construction
- Constructed entirely of stainless steel for strength and corrosion resistance
- Static strength 1,500 lbs.
- Dynamic strength 70 ft-lbs.
- Horizontally adjustable keeper to allow for door and frame misalignment
- 1/2" keeper depth (712 and 732)
- 3/4" keeper depth (712-75 and 732-75)
- Non-handed
- Fail Secure (standard)
- Plug-in connector
- Five year limited warranty

## Optional Features

- Fail Safe
- LBMLCM - Latchbolt & Locking Cam Monitor

## Accessories

- 152 - Universal mounting tabs
- 2001 - Plug-in bridge rectifier
- 2001-1 - Wire-in bridge rectifier
- 2004 - ElectroLynx™ adapter
- 2005 - SMART Pac II™
- 2006P - Plug-in buzzer
- 2003 - MOV

## Finishes

- 630 - Satin stainless steel finish
- 605 - Bright brass finish
- 606 - Satin brass finish
- 612 - Satin bronze finish
- 613 - Bronze toned finish
- 629 - Bright stainless steel finish