### **CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION** OFFICE OF THE STATE FIRE MARSHAL

### FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM



### LISTING SERVICE

LISTING No.

3774-1021:0100

Page 1 of 1

**CATEGORY:** 

3774 -- ELECTRIC LOCKS

LISTEE:

ARCHITECTURAL CONTROL SYSTEMS10666 GATEWAY BLVD, ST LOUIS, MO 63132

Contact: CRAIG HUBER (314) 432-5588 Fax (314) 432-2090

Email: chuber@acsi-inc.com

**DESIGN:** 

Model GEMINI 8500 series. Refer to listee's data sheet for detailed product description and

operational considerations.

**RATING:** 

**INSTALLATION:** 

In accordance with listee's printed installation instructions, applicable codes and ordinances

and in a manner acceptable to the authority having jurisdiction.

MARKING:

Listee's name, model number and UL label.

APPROVAL:

Listed as an electric lock. Authority having jurisdiction should be consulted prior to

installation

NOTE:

Formerly 4138-1021:100

\*Rev. 06-04-2002



CSFM Fire Engineering staff has reviewed This listing is based upon technical data submitted by the applicant. the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational Refer to listee's data sheet, installation instructions and/or other suitable requirements or installation criteria. information sources.

Date Issued:

July 01, 2010

Listing Expires

June 30, 2011

Authorized By:

FRANCIS MATEO, Program Coordinator

Fire Engineering Division

# CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION OFFICE OF THE STATE FIRE MARSHAL

#### FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM





LISTING No.

3774-1021:0102

Page 1 of 1

CATEGORY:

3774 -- ELECTRIC LOCKS

LISTEE:

ARCHITECTURAL CONTROL SYSTEMS10666 GATEWAY BLVD, ST LOUIS, MO 63132

Contact: CRAIG HUBER (314) 432-5588 Fax (314) 432-2090

Email: chuber@acsi-inc.com

**DESIGN:** 

Models M1510C, \*A, and \*B electrically controlled solenoid single point mortise locks.

Refer to listee's data sheet for detailed product description and operational considerations.

**RATING:** 

24 VAC, \*24 VDC, \*12 VAC, \*12 VDC

**INSTALLATION:** 

In accordance with listee's printed installation instructions, applicable codes and

ordinances and in a manner acceptable to the authority having jurisdiction.

MARKING:

Listee's name, model number, electrical rating, and UL label.

APPROVAL:

Listed as 11/2-hour and 3-hour fire-rated electric lock. Authority having jurisdiction should be

consulted before any installations.

NOTE:

Formerly 4136-1021:102

\*Rev. 08-31-2004



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other suitable information sources.

Date Issued:

July 01, 2010

Listing Expires

June 30, 2011

Authorized By:

FRANCIS MATEO, Program Coordinator

Fire Engineering Division

## CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION OFFICE OF THE STATE FIRE MARSHAL

#### FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM





LISTING No.

3774-1021:0103

Page 1 of 1

**CATEGORY:** 

3774 -- ELECTRIC LOCKS

LISTEE:

ARCHITECTURAL CONTROL SYSTEMS10666 GATEWAY BLVD, ST LOUIS, MO 63132

Contact: CRAIG HUBER (314) 432-5588 Fax (314) 432-2090

Email: chuber@acsi-inc.com

**DESIGN:** 

C1510C\* series. Solenoid operated, single point cylindrical locks; for installation in swinging

1-1/2 fire rated composite doors (4' X 8'), and

3-hour fire-rated hollow metal doors (4' X 8'). Refer to listee's data sheet for electrical rating

and operational considerations.

**RATING:** 

12/24 VAC/DC

**INSTALLATION:** 

In accordance with listee's printed installation instructions, applicable codes and ordinances

and in a manner acceptable to the authority having jurisdiction.

MARKING:

Listee's name, model number and UL label.

APPROVAL:

Listed as an electrified single-point lock for use on fire-rated doors. Authority having

jurisdiction should be consulted before any installations.

NOTE:



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other suitable information sources.

Date Issued:

July 01, 2010

Listing Expires

June 30, 2011

Authorized By:

FRANCIS MATEO, Program Coordinator

Fire Engineering Division