



Model 9400

The Easy  
Install,  
Slim-Line,  
Surface  
Mounted  
Solution

[hesinnovations.com](http://hesinnovations.com)



# 9400 Series

## Surface Mounted Electric Strike

Works with rim exit devices with a 1/2" throw latchbolt

### Stylish Looks

#### Slim-Line Profile

Unique 1/2" slim-line form  
Decorative cover for a sleek look  
Available in 6 finishes to match any decor

### Convenient

#### Easy Installation

Completely surface mounted for quick installation  
Installs in metal or wood frames  
Simple fail secure/fail safe and 12/24VDC conversions

### Quality

#### Reliable Strength

Exceeds Grade 1 standards for strength and performance  
UL 1034 burglary-resistant listed  
Components encased in 1/2" stainless steel housing

ASSA ABLOY, the global leader in door opening solutions



RIM EXIT DEVICES



FIELD SELECTABLE  
(12 OR 24VDC)



FIELD SELECTABLE  
(FAIL SECURE/FAIL SAFE)



GRADE 1



OUTDOOR RATED



UL 1034  
BURGLARY LISTED



# 9400 Series

## Surface Mounted Electric Strike

### Features

#### Standard Features

- Installs in metal or wood frames
- Decorative cover for a sleek look
- Stainless steel construction
- Static strength to 1,500 lbs.
- Dynamic strength to 70 ft-lbs.
- Endurance 500,000 cycles
- Field selectable fail secure/fail safe
- Dual voltage 12 or 24VDC
- Non-handed. Horizontal adjustability
- Five year limited warranty

#### Optional Features

- LBM** » Latchbolt monitor
- LBSM** » Latchbolt strike monitor

#### Accessories

- 9400/9500/9600-108** » Spacer plate (black or 630 finish)
- SMB** » Surface mounting box
- 2001M** » Plug-in bridge rectifier
- 2004M** » ElectroLynx® adapter
- 2005M3** » SMART Pac® III
- 2006M** » Plug-in buzzer

#### Finishes

- 630** » Satin stainless steel
- 605** » Bright brass
- 606** » Satin brass
- 612** » Satin bronze
- 613** » Bronze toned
- 629** » Bright stainless steel

### Specifications

#### Listings and Patents

- UL 1034 burglary-resistant listed and suitable for outdoor use
- UL 294 (6th edition) listed
- ANSI/BHMA A156.31, Grade 1
- RoHS compliant
- Patents: 6,392,520 and 8,454,520

#### Frame Application

- Metal
- Wood

#### Electrical (continuous duty)

- .45 Amps @ 12VDC
- .25 Amps @ 24VDC
- PoE friendly

