

**Heavy-duty overhead door holder/stop  
for exterior, vestibule, and interior doors,  
single acting**

**Now available  
US32D & US32**

**7000 SERIES  
SURFACE MOUNTED**



**STANDARD FEATURES**

- For All Stainless Steel Components - Prefix N
- Non-handed/reversible
- Single point hold-open in increments of 5° from 85° to 110°
- Automatic hold-open and release by push and pull on door
- For stop only turn hook mechanism 90°, adjustable spring tension
- 5° to 7° shock compression following hold-open point
- Maximum opening 110°, minimum door thickness 1 1/4"
- Wood, machine screws and grommet nuts included
- Available in all BHMA plated and sprayed finishes

**All Stops  
Warnock Hersey  
listed**

**WHEN ORDERING,  
please list:**

*Model number*

*Door closer number or other  
hardware*

*Mounting means of the door  
and butt size*

*Hold-open or dead-stop  
degree*

*Door opening and thickness*

*Finish*

**SPECIFICATIONS:**

**Stop only function to be  
Warnock Hersey listed as  
manufactured by ABH.**

**Material:**

*Bar 1/2" steel bar; jamb  
bracket stainless steel/  
steel/brass; adjustable  
hold-open tension.*

**STAINLESS STEEL  
SPECIFICATIONS:**

*All parts stainless steel as  
manufactured by ABH.*

DOOR FRAME OPENING		HOLDER NUMBER	
BUTTS OFFSET PIVOTS	CENTER HUNG	HOLD-OPEN	STOP
23" - 28 15/16"	24" - 31 15/16"	7010	7020
29" - 34 15/16"	32" - 38 7/16"	7011	7021
35" - 40 15/16"	38 1/2" - 44 3/16"	7012	7022
41" - 46 15/16"	44 1/4" - 50 3/16"	7013	7023
47" + Greater	50 1/4" - 60"	7014	7024
BHMA NUMBER		C08511	C08541
FED. SPEC TYPE		GJ70	

Contact ABH for special templating or other door opening  
Average weight/unit 2 1/2 lbs.

**www.abhmfg.com**  
**E-mail: abhinfo@abhmfg.com**  
**Architectural Builders Hardware Mfg., Inc.**  
1222 Ardmore Ave., Itasca, IL 60143  
**630.875.9900; FAX 800.9FAXABH (932.9224)**

© 2005 ABH Mfg., Inc.  
Printed in USA 02/05

