



Model 9700



# 9700 Series Surface Mounted Electric Strike

Works with Corbin Russwin SecureBolt™ and Yale SquareBolt® exit devices

The Stylish,  
Windstorm-  
Rated and  
Fire-Rated,  
Square Bolt  
Solution

## Secure

### Reliable Strength

A heavy-duty electric strike for high-security exit devices  
Exceeds all standards for strength and performance  
Windstorm and fire rated

## Convenient

### Easy Installation

Completely surface mounted for quick installation  
Base and cover are separate for easy adjustments  
Field selectable fail safe/fail secure

## Sophisticated

### Stylish Looks

Designed with a stainless steel decorative cover  
Available in 7 finishes to match any decor  
Sleek lines complement ASSA ABLOY exit devices

ASSA ABLOY, the global leader in door opening solutions

hesinnovations.com



RIM EXIT DEVICES



FIELD SELECTABLE  
(12 OR 24VDC)



FIELD SELECTABLE  
(FAIL SECURE/  
FAIL SAFE)



FIRE RATED



GRADE 1



OUTDOOR RATED



UL 1034  
BURGLARY LISTED



ANSI A250.13-2003  
WINDSTORM  
RESISTANT



Designed to work with Yale SquareBolt® Exit Device



# 9700 Series

## Surface Mounted Electric Strike

### Features

#### Standard Features

- Separate base and decorative cover for easy adjustments
- Stainless steel construction
- Independently verified by a nationally recognized testing laboratory
  - *Static strength to 2,000 lbs.*
  - *Dynamic strength to 120 ft-lbs.*
  - *Endurance 1,000,000 cycles*
- Field selectable fail secure/fail safe
- Dual voltage 12 or 24VDC
- Non-handed. Horizontal adjustability
- Five year limited warranty

#### Optional Features

- LBM** » Latchbolt monitor
- LBSM** » Latchbolt strike monitor

#### Accessories

- 9400/9500/9600/9700-108** » Spacer plate (black or 630 finish)
- 9000-MTK** » Metal template kit
- SMB** » Surface mounting box
- 2001M** » Plug-in bridge rectifier
- 2004M** » ElectroLynx® adapter
- 2005M3** » SMART Pac® III
- 2006M** » Plug-in buzzer

#### Finishes

- 630** » Satin stainless steel
- 605** » Bright brass
- 606** » Satin brass
- 612** » Satin bronze
- 613** » Bronze toned
- 613E** » Dark oxidized satin bronze
- 629** » Bright stainless steel

### Specifications

#### Listings and Patents

- UL 10C fire-rated, 3 hour (fail secure only)
- CAN4-S104 (ULC-S104), NFPA-252 and ASTM-E152 fire door conformant
- California Fire Marshall listed
- NFPA 80-07 compliant
- UL Listed to ANSI 250.13 Severe windstorm listed
- Florida Building Code Approved (FL#14307)
- UL 1034 burglary-resistant listed and suitable for outdoor use
- UL 294 (Rev.6) Listed
- ANSI/BHMA A156.31 Grade 1
- RoHs compliant
- Patents: 6,390,520, 6,392,520 and 8,454,520

#### Frame Application

- Metal
- Wood

#### Electrical (continuous duty)

- .45 Amps @ 12 VDC
- .26 Amps @ 24VDC

