

S6000 Spectra™ Series - S6000-DE/KDE/DES Delayed Egress



DELAYED EGRESS

The delayed egress for the Spectra Exit Device is a 2-piece option. The master exit device is electrified and the wall mounted controller adds keypad control and key reset capabilities.



FEATURES

- Code Dependent Exit Delay and Nuisance Times
- Reset, Sustained Bypass and Momentary Bypass by Keypad or Optional Mortise Cylinder

MODELS

- DE** Electrification of Master Exit Device and Wall Mount Controller with Keypad Control & Reset
- KDE** Electrification of Master Exit Device and Wall Mount Controller with Both Keypad and Key Switch Control & Reset, Less Cylinder
- DES** for Pair of Doors, Additional Exit Device Equipped with Delayed Egress Mechanism, Less Controller.
MUST BE ORDERED TOGETHER WITH DE AND DEVICE

SPECIFICATIONS

Exit Delay	15 or 30-Second Exit Delay (Code Dependent)
Nuisance Delay	1 or 2 Second Delay
Voice Annunciation	Digital Countdown Display with Door Indicator
Power Requirements	Single: 24VDC @ 430mA Tandem: 24VDC @ 600mA



HOW TO ORDER:

1| SPECIFY MODEL

- S61** Rim Mount
 - S62** SVR Surface Vertical Rod
 - S63** Mortise (03 Lever trim included)
- Specify: **EE/GE** Eclipse or Galaxy Escutcheon

2| SPECIFY FUNCTION

- 01** Exit Only
- 02** Dummy
- 03** Nightlatch

3| SPECIFY PANIC OR FIRE RATED

- P** Panic Exit Device
- F** Fire Exit Device

4| SPECIFY HAND (FOR S63 ONLY)

- RR** Right Hand Reverse Bevel, RHRB
- LR** Left Hand Reverse Bevel, LHRB

5| SPECIFY FINISH

- U** 630 Dull Stainless Steel

6| SPECIFY LENGTH

- 36** For 36" Door
- 42** For 42" Door
- 48** For 48" Door

7| SPECIFY CONTROLLER

- DE** Electrification of Master Exit Device and Wall Mount Controller with Keypad Control & Reset
- KDE** Electrification of Master Exit Device and Wall Mount Controller with Both Keypad and Key Switch Control & Reset, Less Cylinder
- DES** for Pair of Doors, Additional Exit Device Equipped with Delayed Egress Mechanism, Less Controller. Must be Ordered Together with DE/KDE Device.



8| SPECIFY OPERATION

- NA** IBC, IFC, NFPA Compliant, Field Selectable 15 to 30 Second Exit Delay, 1 or 2 Nuisance Delay
- NC** IBC, IFC, NFPA 101, NFPA 1-UFC, UBC, SBC Compliant, Fixed 15 Second Exit Delay, 0/1 Nuisance Delay, Calif. Building Code OSHPD/Manual Power Up
- ND** IBC, IFC, NFPA 101, NFPA 1-UFC, UBC, SBC Compliant, Fixed 15 second Exit Delay, 0/1 Nuisance Delay
- BC** BOCA National Building Code/City of Chicago Compliant, Fixed 15 Second Exit Delay, 0 Nuisance Delay, Auto Reset 30 Seconds
- BD** BOCA National Building Code, Fixed 15 Second Exit Delay, 0/1 Nuisance Delay, Auto Reset 30 seconds

9| SPECIFY TRIM


FOR MORTISE S63 ONLY

- EE** Eclipse Escutcheon
- GE** Galaxy Escutcheon

9| SPECIFY TRIM (OPTIONAL) RIM, SURFACE ONLY

Mechanical Trim (less cylinder)


- EK02U** Dummy Eclipse Escutcheon
- GK02U** Dummy Galaxy Escutcheon
- EK03U** Eclipse Escutcheon
- GK03U** Galaxy Escutcheon



Electric Trim

- Failsecure, field reversible to failsafe
- 4 ft cable
- 600/300 mA @12/24VDC

- EKE03U** Eclipse style electric trim less mortise cylinder, Stainless Steel Finish
- GKE03U** Galaxy style electric trim less mortise cylinder, Stainless Steel Finish



- CP01** 6-pin Rim Cylinder, Keyed Different, Specifically For EK03, GK03 and SP03

10| SPECIFY OPTIONS FOR CONTROLLER

- DEC-J** 3 Gang Interior-101-DEC
- SHD-J** Shroud for Outdoor Use DEC-J



ACCESSORIES

- PTH-4Q** Four Wire, Dull Chrome
- PTH-4QDPS** Four Wire w/DPS, Dull Chrome
- PTH-10Q** Ten Wire, Dull Chrome

- MC-4PAK**
Frame Mounted DPS -
10 pack



- PTM-10AL** Ten Wire Aluminum Powder Coat, US28 equivalent
- PTM-10BZ** Ten Wire Aluminum Powder Coat, US10B equivalent, Dark Brown Powder Coat

