

# RIXSON 609 Overhead Concealed Door Closer

The global leader in  
door opening solutions

**ASSA ABLOY**



## Features

- Medium-duty cast iron closer
- Adjustable spring size 1-3
- Double acting
- Center hung
- End load arms
- Non-handed
- Optional hold open assembly built into closer
- Separate closing and latching valves
- 5mm extended spindle
- All weather fluid



Door Rail Adjustable  
End Load Bottom Pivot



End Load 609 Arm

## Technical Specifications

### Materials:

- Cast iron closer body
- Radial ball bearing bottom pivot

### System Includes:

- Closer (OHC-609)
  - 90° Back Stop, Non -Hold Open (OHC-609-90NHO)
  - 90° Back Stop, Hold Open (OHC-609-90HO)
  - 105° Back Stop, Non-Hold Open (OHC-609-105NHO)
  - 105° Back Stop, Hold Open (OHC-609-105HO)
- Closer mounting clips pre-installed into finished header tube
  - Header specified separately

### Pivot Options:

- Door Rail Adjustable End Load Bottom Pivot (PV-ENDLOAD)
- Patch Fitting Floor Mounted Pivot (PF-FM-PIVOT)
- Patch Fitting Adjustable Pivot (PF-ADJ-PIV)

### Accessories:

- Mounting Clips (OHC-609-MC)
- End Load Arm (OHC-609-ARM)

### Approvals and Listings:

- ANSI/BHMA standard A156.4, Grade 1
- UL / cUL listed for use on fire rated doors
- UL10C listed for positive pressure fire test
- Barrier free operation to comply with Federal Accessibility Standards (ADA); complying with ANSI A117.1 with center pivoted applications

### Door Specifications:

- Maximum door weight: 200 lbs.
- Maximum door width: interior 42", exterior 36"

ASSA ABLOY Glass Solutions  
300 Main Street  
Rockwood, PA 15557  
PH: (855) 594-6989  
www.assaabloyglass.us

ASSA ABLOY is the global leader in door opening solutions, dedicated to satisfying end-user needs for security, safety and convenience