



Glass Panic Device Comparison Sheet

The global leader in
door opening solutions

ASSA ABLOY

Glass Panic Device Comparison Sheet

Product Features	CRL/Blumcraft (PA100)	ASSA ABLOY (PDU8000)
End Type	<ul style="list-style-type: none"> Bent End, matches bent end style pulls 	<ul style="list-style-type: none"> Post Mounted, matches ladder style pulls
Push Region	Finish modification surrounding "PUSH" letters <ul style="list-style-type: none"> Visual Tactile 	Engraved "PUSH" with Grooved boundary lines. <ul style="list-style-type: none"> Visual Tactile Pass UL/ANSI Standards
Aesthetics	<ul style="list-style-type: none"> Unique wide radius 	<ul style="list-style-type: none"> Radius matches other ASSA ABLOY Rockwood products.
California Building & ADA Codes requiring operable parts to be within 10" vertically*	<ul style="list-style-type: none"> 10.5" from push bar to centerline of key 	<ul style="list-style-type: none"> 9" from push bar to key centerline
Force to Open		<ul style="list-style-type: none"> Less than 5lbs of force
Latch Design	<ul style="list-style-type: none"> Roller Latch 	<ul style="list-style-type: none"> Flat Latch enhances security Engraved engagement lines to assist in proper installment.
Certifications	<ul style="list-style-type: none"> ANSI/BHMA 156.3-2008 UL 305 CAN/ULC-S132-07 	<ul style="list-style-type: none"> ANSI/BHMA 156.3-2008 UL 305 CAN/ULC-S132-07 Complies to ANSI/BHMA 156.3-2014
Installation Features	<ul style="list-style-type: none"> Specialized Tools Required (Spanner Wrench) 	<ul style="list-style-type: none"> No Specialized tools required Latch engagement lines Pivot posts with pin feature C-Bushing gives 1/8" more adjustment
Adjustability	<ul style="list-style-type: none"> Latch 	<ul style="list-style-type: none"> Latch C-Bushings Strike Shims
Dogging Feature	<ul style="list-style-type: none"> Standard 	<ul style="list-style-type: none"> Optional
Manual Strike	<ul style="list-style-type: none"> Stainless steel 	<ul style="list-style-type: none"> Stainless steel Nylon coated (keeper region)
Environmental		<ul style="list-style-type: none"> Produced in ISO 14001 facility
Packaging	<ul style="list-style-type: none"> Large crates 	<ul style="list-style-type: none"> Medium crates Full height mating pulls sent separately

*2016 California Building Code 11B-404.2.7:

"Shall comply with (ADA) Section 11B-309.4. Operable parts of such hardware shall be 34 inches minimum and 44 inches maximum above the finished floor"

For the above to be possible the crash bar must be positioned within 10" of the cylinder

CRL/Blumcraft (PA100)



Bent End, matches bent end style pulls



Finish modification surrounding "PUSH" letters

ASSA ABLOY (PDU8000)



Post Mounted, matches ladder style pulls



Engraved "PUSH" with grooved boundary lines



Engraved engagement lines to assist in proper installment

ASSA ABLOY Glass Solutions
300 Main Street
Rockwood, PA 15557
855-594-6989
www.assaabloyglass.us

ASSA ABLOY is the global leader in door opening solutions, dedicated to satisfying end-user needs for security, safety and convenience