



MT20

Multi-technology enrollment reader with ENGAGE™ technology

Overview

The Schlage® MT20 USB multi-technology enrollment reader with ENGAGE™ technology is designed to simplify your enrollment process. The MT20 simplifies the enrollment of proximity, smart or mobile credentials in an access control system by using a computer's USB connection. The MT20 does not require software to operate when using a USB connection and will function on any operating system. When using the ENGAGE Web Application, the MT20 will automatically output the data in the expected format. The USB connection emulates a keyboard and will keystroke the facility code and badge ID from the credential to the cursor's location on the screen.

The MT20 is compatible with Schlage smart credentials (MIFARE Classic®, MIFARE Plus® and MIFARE® DESFire® EV1), Schlage and aptiQ® mobile credentials and most proximity credentials.



Features and benefits

- Use your computer and the ENGAGE web app to easily enroll credentials in your access control system
- Recognizes Schlage smart credentials (MIFARE Classic, MIFARE Plus and MIFARE DESFire EV1), Schlage and aptiQ mobile credentials and most proximity credentials
- Limited Lifetime Warranty



Model	MT20
Reader type	USB
Software and operating system requirements	N/A - USB
Bit formats recognized	26A, 32X, 34N, 34S, 35C, 37X, 37H, 40X
Technologies supported	Schlage Proximity XceedID® Proximity HID® Proximity GE/CASI ProxLite® AWID® Proximity LenelProx® Schlage MIFARE Classic Secure Sector aptiQ/XceedID MIFARE Classic Secure Sector Schlage MIFARE Plus Secure Sector Schlage MIFARE DESFire EV1 with PACSA Secure Sector aptiQ MIFARE DESFire EV1 with PACSA Secure Sector DESFire® CSN HID iClass® CSN Inside Contactless PicoTag® CSN ST Microelectronics® CSN Texas Instruments Tag-It® Serial Number Phillips I-Code® CSN
Physical dimensions (L x W x H)	5.56 " x 2.00 " x .695 "
Operating temperatures	32° to 104° F (0° to 40° C)
Weight	4.1 oz
Power supply	Connect to powered USB port or via USB power supply
Interface	USB
Current requirement	160 mA
Default configuration	CE-401-073, for use with ENGAGE web applicaton
Octal output	CE-401-061, for use with SMS Express
FC/BID output	CE-401-060 (SUSB89 default,) for use as keystroke emulator
BID only	CE-401-069, for use as keystroke emulator

Allegion, the Allegion logo, aptiQ, aptiQmobile, Schlage, the Schlage logo and XceedID, are trademarks of Allegion plc, its subsidiaries and/or affiliates in the United States and other countries. All other trademarks are the property of their respective owners.

About Allegion

Allegion (NYSE: ALLE) is a global pioneer in safety and security, with leading brands like CISA®, Interflex®, LCN®, Schlage®, SimonsVoss® and Von Duprin®. Focusing on security around the door and adjacent areas, Allegion produces a range of solutions for homes, businesses, schools and other institutions. Allegion is a \$2 billion company, with products sold in almost 130 countries. For more, visit www.allegion.com.

KRYPTONITE ■ LCN ■  ■ STEELCRAFT ■ VON DUPRIN



© 2017 Allegion
010523, Rev. 9/17
www.allegion.com/us