Overhead Holders & Stops

3300A Series Surface Mount, Medium Duty, Adjustable





Standard Features

- Surface mount
- Medium duty
- Stop, hold-open and friction functions available
- Single acting doors only
- Non-handed
- For interior use on moderate traffic and medium weight doors
- Degree of opening is field-adjustable after installation from 85° to 110° (5° increments)
- Shock absorbing spring provides 3° to 5° cushion before dead-stop
- Standard fasteners supplied with sex bolts for 1-34" to 1-78" thick door (see options for other door thicknesses)
- UL Listed as Miscellaneous Fire Door Accessories for use on wood fire doors rated up to 90 minutes and metal fire doors rated up to 3 hours (stop function only)
- Average weight per unit = 3 lbs.

Door Frame Opening	Model Number		
Hinges or Offset Pivots	Hold Open	Stop	Friction
24" - 29-15/16"	3311A	3321A	3331A
30" - 35-15/16"	3312A	3322A	3332A
36" - 42"	3313A	3323A	3333A
ANSI Code	C05511	C05541	C05531

Options Available

(see page B-5 for details)

- **THICK** Fasteners for doors other than 1-34" to 1-78" thick - Specify door thickness
- **SEC** Security fasteners
- AJB 44443 Angle Jamb Bracket for pull side mount or push side flush mount
- LL For lead-lined door applications
- **CL** For use with cam lift hinges
- LS Less shock-absorbing spring for special applications
- N All stainless steel (non-ferrous) components for wet environments to prevent corrosion
- T Jamb bracket is replaced with a threaded pivot screw and nylon washer
- **HC** Hold closed
- SPECIAL Contact ABH if the dimensions, hardware, or specifications differ from what is shown on the template or if additional hardware is being used at the top of the door. A custom application and/or unit may be required.
- If using a closer, please go to our website and reference "ABH Overhead Holder & Stop Compatibility Chart" to determine possible conflict.

Material

Stainless steel is the standard base material for arm, channel and jamb bracket for all finishes.

Specify When Ordering

- Model Number
- Finish
- Option(s), if applicable



