## Overhead Holders & Stops

## 4000 Series Concealed Mount, Medium Duty





- Concealed mount
- Medium duty
- Stop, hold-open and friction functions available
- Single or double acting doors
- Non-handed
- For interior use on moderate traffic and medium weight doors
- Standard installation from 85° to 110° of opening (5° increments)
- Shock absorbing spring provides 3° to 5° cushion before dead-stop
- 1-3/8" minimum door thickness
- UL Listed as Miscellaneous Fire Door Accessories for use on wood fire doors rated up to 90 minutes and metal fire doors rated up to 3 hours (stop function only)
- Average weight per unit = 2 lbs.

Door Frame Opening		Model Number		
Hinges, Swing Clear or Offset Pivots	Center Hung	Hold Open	Stop	Friction
18" - 23-15/16" *	-	4011	4021	4031
24" - 29-15/16"	-	4012	4022	4032
30" - 35-15/16"	32" - 37-15/16"	4013	4023	4033
36" - 48"	38" - 48"	4014	4024	4034
ANSI Code		C04511	C04541	C04531

<sup>\*</sup> Butt Hinges only for this size



(see page B-5 for details)

- SEC Security fasteners
- LL For lead-lined door applications
- N All stainless steel (non-ferrous) components for wet environments to prevent corrosion
- T Threaded pivot screw and nylon washer to replace jamb bracket
- HC Hold Closed
- SPECIAL Contact ABH if the dimensions, hardware or specifications differ from what is shown on the template or if additional hardware is being used at the top of the door. A custom application and/or unit may be required.
- If using a closer, please go to our website and reference "ABH Overhead Holder & Stop Compatibility Chart" to determine possible conflict.

## **Material**

• Stainless steel is the standard base material for arm, channel and jamb bracket for all finishes.

## **Specify When Ordering**

- Model Number
- Finish
- Option(s), if applicable



ACCESS HARDWARE SUPPLY accesshardware.com