

Overhead Holders & Stops



Innovation, Quality,
Customer Service...

7000 Series Surface Mount, Heavy Duty



Standard Features

- Surface mount
- Heavy duty
- Stop and hold-open functions available
- Single acting doors only
- Non-handed
- For interior or exterior use on frequent traffic and heavy weight doors
- Standard installation from 85° to 110° of opening (5° increments)
- Shock absorbing spring provides 3° to 5° cushion before dead-stop
- Standard fasteners supplied with sex bolts for 1-3/4" to 2" thick door (see options for other door thicknesses)
- UL Listed as Miscellaneous Fire Door Accessories for use on wood fire doors rated up to 90 minutes and metal fire doors rated up to 3 hours (stop function only)
- Average weight per unit = 3 lbs.

Options Available

(see page B-5 for details)

- **THICK** - Fasteners for doors other than 1-3/4" to 2" thick
- Specify door thickness
- **SEC** - Security fasteners
- **AJB** - 70377 Angle jamb bracket for pull side mount or push side flush mount
- **LL** - For lead-lined door applications
- **N** - All stainless steel (non-ferrous) components for wet environments to prevent corrosion
- **SPECIAL** - Contact ABH if the dimensions, hardware or specifications differ from what is shown on the template or if additional hardware is being used at the top of the door. A custom template and/or unit may be required.
- If using a closer, please go to our website and reference "ABH Overhead Holder & Stop Compatibility Chart" to determine possible conflict

Door Frame Opening		Model Number	
Hinges or Offset Pivots	Center Hung	Hold Open	Stop
23" - 28-15/16"	24" - 31-15/16"	7010	7020
29" - 34-15/16"	32" - 38-7/16"	7011	7021
35" - 40-15/16"	38-1/2" - 44-3/16"	7012	7022
41" - 46-15/16"	44-1/4" - 50-3/16"	7013	7023
47" - 54"	50-1/4" - 60"	7014	7024
ANSI Code		C08511	C08541

Material

- **Stainless steel** is the standard base material for jamb bracket and door bracket on all finishes (bar is cold rolled steel, cad plated).

Specify When Ordering

- Model Number
- Finish
- Option(s), if applicable

DISTRIBUTED BY



B-16 2014 ABH Mfg., Inc.

Architectural Builders Hardware Manufacturing, Inc.
1222 Ardmore Avenue, Itasca, IL 60143
Tel: 630-875-9900 • Fax: 630-875-9918 / 800-932-9224
Web: www.abhmfg.com • Email: abhinfo@abhmfg.com

