

# Overhead Holders & Stops



Innovation, Quality,  
Customer Service...

## 9000 Series Surface Mount, Heavy Duty



### Standard Features

- Surface mount
- Heavy duty
- Stop, hold-open and friction functions available
- Single acting doors only
- Non-handed
- For interior or exterior use on frequent traffic and heavy weight doors
- Standard installation from 85° to 110° of opening (5° increments)
- Shock absorbing spring provides 3° to 5° cushion before dead-stop
- Standard fasteners supplied with sex bolts for 1-3/4" to 2-1/4" thick door (see options for other door thicknesses)
- UL Listed as Miscellaneous Fire Door Accessories for use on wood fire doors rated up to 90 minutes and metal fire doors rated up to 3 hours (stop function only)
- Average weight per unit = 5 lbs.

### Options Available

(see page B-5 for details)

- **THICK** - Fasteners for doors other than 1-3/4" to 2-1/4" thick - Specify door thickness
- **SEC** - Security fasteners
- **AJB** - 90541 Angle jamb bracket for pull side mount or push side flush mount
- **LL** - For lead-lined door applications
- **LS** - Less shock-absorbing spring for special applications
- **N** - All stainless steel (non-ferrous) components for wet environments to prevent corrosion
- **T** - Threaded pivot screw and nylon washer to replace jamb bracket
- **HC** - Hold Closed
- **CL** - For use with cam lift hinges
- **SPECIAL** - Contact ABH if the dimensions, hardware or specifications differ from what is shown on the template or if additional hardware is being used at the top of the door. A custom template and/or unit may be required.
- If using a closer, please go to our website and reference "ABH Overhead Holder & Stop Compatibility Chart" to determine possible conflict.

### Material

- **Stainless steel** is the standard base material for arm, channel and jamb bracket for all finishes.

### Specify When Ordering

- Model Number
- Finish
- Option(s), if applicable

Door Frame Opening		Model Number		
Hinges, Swing Clear or Offset Pivots	Center Hung	Hold Open	Stop	Friction
24" - 27-15/16"	26" - 29-15/16"	9018	9028	9038
28" - 29-15/16"	30" - 33-15/16"	9011	9021	9031
30" - 31-15/16"	34" - 35-15/16"	9012	9022	9032
32" - 35-15/16"	36" - 38-15/16"	9013	9023	9033
36" - 39-15/16"	39" - 40-15/16"	9014	9024	9034
40" - 41-15/16"	41" - 44-15/16"	9015	9025	9035
42" - 43-15/16"	45" - 46-15/16"	9016	9026	9036
44" - 54"	47" - 56"	9017	9027	9037
ANSI Code		C02511	C02541	C02531



Architectural Builders Hardware Manufacturing, Inc.  
1222 Ardmore Avenue, Itasca, IL 60143  
Tel: 630-875-9900 • Fax: 630-875-9918 / 800-932-9224  
Web: www.abhmfg.com • Email: abhinfo@abhmfg.com

DISTRIBUTED BY



2014 ABH Mfg., Inc.

B-19