

**8400 Commercial protection plates**  
**8402 UL Commercial protection plates**

- Door protection plates are available in .050" thick brass, stainless steel or aluminum; and 1/8" thick high impact polyethylene in clear or black.
- All plates, metal and plastic, come standard with four beveled edges and countersunk mounting holes (B-CS).
- Protection plates must be ordered in 1/2" increments. Available in other sizes, consult customer service
- For 8402 UL Plates, UL mark appears in upper right corner. Not available on plastic protection plates.

**Certifications**

- Meets ANSI A156.6 for J301
- UL protection plates certified to UL10C

**Mounting**

- Standard mounting package, 16 per pack
  - #6 X 5/8 oval head screws
- Optional TEK/TORX package, specify TK-TX
  - #6 X 5/8 Self-drilling, Self-tapping screws
  - #6 X 5/8 Torx screws

**Finishes**

- Aluminum 5005 Series, Brass C26800 Series, Stainless Steel 300 Series, Plastic

BHMA	Description	Substrate	Finish	Max sizes
605	Bright Brass	Brass	US3	24"X48"
606	Satin Brass	Brass	US4	24"X48"
612	Satin Bronze	Brass	US10	24"X48"
613	Oil rubbed Bronze	Brass	US10B	36"X48"
619	Satin Nickel	Brass	US15	24"X48"
625	Bright Chrome	Brass	US26	36"X48"
626	Satin Chrome	Brass	US26D	24"X48"
628	Satin Aluminium	Aluminium	US28	48"X48"
629	Bright Stainless Steel	Stainless Steel	US32	48"X48"
630	Satin Stainless Steel	Stainless Steel	US32D	48"X48"
654	Satin Stainless Steel	Stainless Steel	US32D	48"X48"
BLK	Matte black	Stainless Steel	BLK	24"X48"
P-BLK	Black	Plastic	P-BLK	48"X48"
CLR	Clear	Plastic	CLR	48"X48"

- Custom finishes are available as engineering special, consult customer service.

**Available options**

- Specify B-NH for no mounting holes. (Not available on 8402. Available only with US32D, US32, US3, US4, US28, Clear, Black only)
- Specify B-NHA for no mounting holes with adhesive.
- Specify ERS prepped with extra row of screws.
- Special Cut-outs are available as engineering special, consult customer service.

**Available accessory**

- Gasket tape kit tape is recommended when using a brass plate on a metal door to reduce tarnishing from electrolytic oxidation. One tape pack will cover an the perimeters of a 8" x 34" kickplate. Order 8401 gasket tape.



Number of screw packs required by plate size (specify TEK Screws or TORK screws)

	22"-25"	26"-33"	34"-41"	42"-48"
4"-8"	1	1	1	1
9"-16"	1	1	1	1
17"-24"	1	1	1	2
25"-32"	1	1	2	2
33"-40"	1	2	2	2
41"-48"	2	2	2	2

A Hinges & pivots

B47 Pulls & plates

C Flush bolts & coordinators

D Latches, catches & bolts

E Stops

F Exterior hardware

G Miscellaneous hardware